Posted by renton on Sun, 24 Aug 2008 18:45:08 GMT
View Forum Message <> Reply to Message

* mount --bind
* mount -t proc
* mount -t devpts
?

* devpts - 212

```
  PID USER      PR  NI  VIRT  RES  SHR S %CPU %MEM    TIME+  COMMAND
 3738 root      25   0  7900  576  472 R  105  0.0   1:08.20 mount -t proc proc
/home/blabla/user455/proc
```

```
strace mount -t proc proc /home/blabla/user455/proc
execve("/bin/mount", ["mount", "-t", "proc", "proc", "/home/blabla/user455/pr"...], [/* 27 vars */]) = 0
brk(0)                                  = 0x610000
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb762e4000
uname({sys="Linux", node="l5v1.in-solve.ru", ...}) = 0
access("/etc/ld.so.preload", R_OK)      = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY)      = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=24559, ...}) = 0
mmap(NULL, 24559, PROT_READ, MAP_PRIVATE, 3, 0) = 0x2aeb762e5000
close(3)                                = 0
open("/lib/libblkid.so.1", O_RDONLY)    = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\20;\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=42832, ...}) = 0
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb762eb000
mmap(NULL, 2138136, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2aeb764e5000
mprotect(0x2aeb764ee000, 2093056, PROT_NONE) = 0
```

```
mmap(0x2aeb766ed000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x8000) = 0x2aeb766ed000
mmap(0x2aeb766ef000, 24, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2aeb766ef000
close(3)                                = 0
open("/lib/libuuid.so.1", O_RDONLY)     = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\27\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=18768, ...}) = 0
mmap(NULL, 2113936, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2aeb766f0000
mprotect(0x2aeb766f4000, 2093056, PROT_NONE) = 0
mmap(0x2aeb768f3000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3000) = 0x2aeb768f3000
close(3)                                = 0
open("/lib/libc.so.6", O_RDONLY)        = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\220\334\1\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=1293456, ...}) = 0
mmap(NULL, 3399928, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2aeb768f5000
mprotect(0x2aeb76a2b000, 2093056, PROT_NONE) = 0
mmap(0x2aeb76c2a000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x135000) = 0x2aeb76c2a000
mmap(0x2aeb76c2f000, 16632, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2aeb76c2f000close(3)
        = 0
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb76c34000
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb76c35000
arch_prctl(ARCH_SET_FS, 0x2aeb76c34de0) = 0
mprotect(0x2aeb76c2a000, 16384, PROT_READ) = 0
mprotect(0x2aeb768f3000, 4096, PROT_READ) = 0
mprotect(0x2aeb766ed000, 4096, PROT_READ) = 0
mprotect(0x60d000, 4096, PROT_READ)     = 0
mprotect(0x2aeb764e3000, 4096, PROT_READ) = 0
munmap(0x2aeb762e5000, 24559)           = 0
brk(0)                                  = 0x610000
brk(0x631000)                           = 0x631000
umask(022)                              = 022
open("/dev/null", O_RDWR)               = 3
close(3)                                = 0
getuid()                                = 0
geteuid()                               = 0
lstat("/etc/mtab", {st_mode=S_IFLNK|0777, st_size=12, ...}) = 0
stat("/sbin/mount.proc", 0x7fff347dd090) = -1 ENOENT (No such file or directory)
rt_sigprocmask(SIG_BLOCK, ~[TRAP SEGV RTMIN RT_1], NULL, 8) = 0
stat("/sbin/mount.proc", 0x7fff347dd090) = -1 ENOENT (No such file or directory)
mount("proc", "/home/blabla/user455/proc", "proc"..., MS_MGC_VAL, NULL
```

```
mmap(0x2aeb766ef000, 24, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2aeb766ef000
close(3)                                = 0
open("/lib/libuuid.so.1", O_RDONLY)     = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\27\0\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=18768, ...}) = 0
mmap(NULL, 2113936, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2aeb766f0000
mprotect(0x2aeb766f4000, 2093056, PROT_NONE) = 0
mmap(0x2aeb768f3000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3000) = 0x2aeb768f3000
close(3)                                = 0
open("/lib/libc.so.6", O_RDONLY)        = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\220\334\1\0\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=1293456, ...}) = 0
mmap(NULL, 3399928, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2aeb768f5000
mprotect(0x2aeb76a2b000, 2093056, PROT_NONE) = 0
mmap(0x2aeb76c2a000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x135000) = 0x2aeb76c2a000
mmap(0x2aeb76c2f000, 16632, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2aeb76c2f000
close(3)                                = 0
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb76c34000
mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x2aeb76c35000
arch_prctl(ARCH_SET_FS, 0x2aeb76c34de0) = 0
mprotect(0x2aeb76c2a000, 16384, PROT_READ) = 0
mprotect(0x2aeb768f3000, 4096, PROT_READ) = 0
mprotect(0x2aeb766ed000, 4096, PROT_READ) = 0
mprotect(0x60d000, 4096, PROT_READ)     = 0
mprotect(0x2aeb764e3000, 4096, PROT_READ) = 0
munmap(0x2aeb762e5000, 24559)           = 0
brk(0)                                  = 0x610000
brk(0x631000)                           = 0x631000
umask(022)                              = 022
open("/dev/null", O_RDWR)               = 3
close(3)                                = 0
getuid()                                = 0
geteuid()                               = 0
lstat("/etc/mtab", {st_mode=S_IFLNK|0777, st_size=12, ...}) = 0
stat("/sbin/mount.proc", 0x7fff347dd090) = -1 ENOENT (No such file or directory)
rt_sigprocmask(SIG_BLOCK, ~[TRAP SEGV RTMIN RT_1], NULL, 8) = 0
stat("/sbin/mount.proc", 0x7fff347dd090) = -1 ENOENT (No such file or directory)
mount("proc", "/home/blabla/user455/proc", "proc"..., MS_MGC_VAL, NULL
```