Posted by ivan_v on Tue, 04 Nov 2008 20:01:26 GMT
View Forum Message <> Reply to Message

HW - Alt Linux 2.6.18-ovz-smp-alt14
VE - Debian 4.0.1

vzctl version 3.0.23

[root@alt-03 /]# cat /etc/vz/conf/200[12].conf | grep NETIF
NETIF=" ifname=eth0,mac=52:54:00:01:52:F0,host_ifname=veth2001.0,hos
t_mac=52:54:00:01:52:F0 "
NETIF=" ifname=eth0,mac=52:54:00:DE:CE:98,host_ifname=veth2002.0,hos
t_mac=52:54:00:DE:CE:98 "

[root@alt-03 ~]# cat /vz/private/200[12]/etc/network/interfaces | grep -v "#"
auto eth0 venet0 lo
iface eth0 inet static
	address 192.168.100.10
	netmask 255.255.255.0
	broadcast 192.168.100.255
iface venet0 inet static
	address 127.0.0.1
	netmask 255.255.255.255
	broadcast 0.0.0.0
iface lo inet loopback

auto eth0 venet0 lo
iface eth0 inet static
	address 192.168.100.11
	netmask 255.255.255.0
	broadcast 192.168.100.255
iface venet0 inet static
	address 127.0.0.1

```
        netmask 255.255.255.255
        broadcast 0.0.0.0
iface lo inet loopback


bridge name  bridge id           STP enabled     Interfaces
vmbr0        8000.000000000000   yes


[root@alt-03 ~]# vzctl start 2001
Starting container ...
Container is mounted
Setting CPU units: 1000
Setting CPUs: 1
Configure meminfo: 65536
Configure veth devices: veth2001.0
Adding interface veth2001.0 to bridge vmbr0 on CT0 for CT2001
Container start in progress...

[root@alt-03 ~]# vzctl start 2002
Starting container ...
Container is mounted
Setting CPU units: 1000
Setting CPUs: 1
Configure meminfo: 65536
Configure veth devices: veth2002.0
Adding interface veth2002.0 to bridge vmbr0 on CT0 for CT2002
Container start in progress...



bridge name  bridge id         STP enabled     interfaces
vmbr0        8000.5254000152f0 yes             veth2001.0
                                               veth2002.0
```

```
2001:/# ifconfig
eth0      Link encap:Ethernet  HWaddr 52:54:00:01:52:F0
          inet addr:192.168.100.10  Bcast:192.168.100.255  Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:6 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:0 (0.0 b)  TX bytes:168 (168.0 b)
```

```
2002:/# ifconfig
eth0      Link encap:Ethernet  HWaddr 52:54:00:DE:CE:98
          inet addr:192.168.100.11  Bcast:192.168.100.255  Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:6 errors:0 dropped:0 overruns:0 frame:0
          TX packets:6 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:168 (168.0 b)  TX bytes:168 (168.0 b)
```