
Subject: Re: Ethernet bonding with bridge device on CentOS 5.3

Posted by [batfastad](#) on Tue, 20 Oct 2009 21:29:25 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi ramjet

Thanks for the info - good news that this is possible!

Yes I want all VEs and the host to be on the same subnet.

No iptables and no tagged VLAN

Yeah I would really appreciate a bit more info on this though if that's ok

Quote:Then add your bond0 and the veth devices of your servers to the bridge. Make sure the bridge is up - either `ifconfig br0 0` or `ifconfig br0 up` and enable forwarding for br0 in `/proc`.

So create the bond per this guide... <http://wiki.openvz.org/Bonding>

Then create the bridge, add VEs to the bridge, add the bond to the bridge

So following this guide... http://wiki.openvz.org/Veth#Virtual_Ethernet_devices_can_be_joined_in_one_bridge

These are the commands I'll need to run:

```
[host-node]# brctl addbr vzbr0
```

```
[host-node]# brctl addif vzbr0 veth102.0
```

```
[host-node]# brctl addif vzbr0 veth103.0
```

```
[host-node]# brctl addif vzbr0 bond0
```

```
[host-node]# ifconfig vzbr0 0
```

```
[host-node]# echo 1 > /proc/sys/net/ipv4/conf/vzbr0/forwarding
```

```
[host-node]# echo 1 > /proc/sys/net/ipv4/conf/vzbr0/proxy_arp
```

But possibly missing the proxy_arp bit... what's the proxy_arp for?

Just read up about it and not sure if I'll need it or not. Doesn't the switch normally deal with arp/mac address/ip translation?

One VE will be a zimbra mail container.

Another will be a Samba/Netatalk/Apache/MySQL container which is our combined NAS/intranet DB system.

Sounds like something like Samba might need proxy_arp enabled for broadcasting whatever it needs to broadcast.

And would I need to do this bit?

http://wiki.openvz.org/Veth#Add_routes_in_CT0

I'm guessing I'd still need to do that but its only for the VE addresses, nothing to do with the bond0

Thanks for all your help... so far
