Subject: Bootlader
Posted by revhost on Sat, 26 Mar 2011 10:19:32 GMT
View Forum Message <> Reply to Message

Hi i changed to openvz on about 6 of my server and one of them that is runnig centos 5.5 i carnt change to bootloader to boot in openvz kernal. Can some one help me with the ssh command and how to do it.

bit of my system info here.

```
  You have a /boot partition.  This means that
#         all kernel and initrd paths are relative to /boot/, eg.
#         root (hd0,0)
#         kernel /vmlinuz-version ro root=/dev/VolGroup01/LogVol00
#         initrd /initrd-version.img
#boot=/dev/mapper/pdc_bfiahedhf
default=1
timeout=5
splashimage=(hd0,0)/grub/splash.xpm.gz
hiddenmenu
title CentOS (2.6.18-238.5.1.el5.028stab085.3)
        root (hd0,0)
        kernel /vmlinuz-2.6.18-238.5.1.el5.028stab085.3 ro root=/dev/VolGroup01/LogVol00 rhgb
quiet
        initrd /initrd-2.6.18-238.5.1.el5.028stab085.3.img
title CentOS (2.6.18-194.32.1.el5xen)
        root (hd0,0)
        kernel /xen.gz-2.6.18-194.32.1.el5
        module /vmlinuz-2.6.18-194.32.1.el5xen ro root=/dev/VolGroup01/LogVol00 rhgb quiet
        module /initrd-2.6.18-194.32.1.el5xen.img
title CentOS (2.6.18-194.el5xen)
        root (hd0,0)
        kernel /xen.gz-2.6.18-194.el5
        module /vmlinuz-2.6.18-194.el5xen ro root=/dev/VolGroup01/LogVol00 rhgb quiet
        module /initrd-2.6.18-194.el5xen.img
```

dont no if i completely cocked it up im new to all this.

thanks.