Subject: [PATCH 3/4] add initlog feature to manual page
Posted by dietmar on Tue, 20 Sep 2011 05:17:17 GMT
View Forum Message <> Reply to Message

From: Dietmar Maurer <dietmar@proxmox.com>

Signed-off-by: Dietmar Maurer <dietmar@proxmox.com>
---
 man/ctid.conf.5 | 5 +++++
 1 files changed, 5 insertions(+), 0 deletions(-)

diff --git a/man/ctid.conf.5 b/man/ctid.conf.5
index d3ec3d0..ecda4ae 100644
--- a/man/ctid.conf.5
+++ b/man/ctid.conf.5
@@ -30,6 +30,11 @@ Specifies whether this container will be started during system boot.
 Default is \fBno\fR, meaning the container will not be started
 if \fBONBOOT\fR parameter is omitted.
 Corresponds to the \fB--onboot\fR option.
+.IP \fBINITLOG\fR="\fByes\fR|\fBno\fR"
+If enabled init output is logged to /var/log/init.log. An additional process started
+inside the container (init-logger) reads the output from init and writes it
+to /var/log/init.log.
+Corresponds to the \fB--initlog\fR option.
 .IP \fBBOOTORDER\fR="\fInumber\fR"
 Specifies the CT boot order priority. Corresponds to the
 \fB--bootorder\fR option.
--
1.5.6.5