Subject: [PATCH 0/4] SUNRPC: pass network namespace context to sockaddr construction routines
Posted by Stanislav Kinsbursky on Wed, 07 Dec 2011 11:21:16 GMT
View Forum Message <> Reply to Message

This is another precursor patch set aimed to remove hard-coded "init_net"
reference from SUNRPC sockaddr convertion and construction routines.

The following series consists of:

Stanislav Kinsbursky (4):
    SUNRPC: use passed network namespace context in rpc_parse_scope_id()
    SUNRPC: use passed network namespace context in rpc_pton6()
    SUNRPC: use passed network namespace context in rpc_pton()
    SUNRPC: use passed network namespace context in rpc_uaddr2sockaddr()

```
 fs/nfs/dns_resolve.c        |    4 ++--
 fs/nfs/nfs4filelayoutdev.c  |    2 +-
 fs/nfs/nfs4namespace.c      |    2 +-
 fs/nfs/super.c              |    4 ++--
 fs/nfsd/nfs4state.c         |    2 +-
 fs/nfsd/nfsctl.c            |    2 +-
 include/linux/sunrpc/clnt.h |    4 ++--
 net/sunrpc/addr.c           |   24 ++++++++++++++++++------------
 net/sunrpc/rpcb_clnt.c      |    2 +-
 net/sunrpc/svcauth_unix.c   |    2 +-
 10 files changed, 25 insertions(+), 23 deletions(-)
```

--
Signature