Subject: [PATCH v5 02/14] memcg: Reclaim when more than one page needed.
Posted by Glauber Costa on Tue, 16 Oct 2012 10:16:39 GMT
View Forum Message <> Reply to Message

From: Suleiman Souhlal <ssouhlal@FreeBSD.org>

mem_cgroup_do_charge() was written before kmem accounting, and expects
three cases: being called for 1 page, being called for a stock of 32
pages, or being called for a hugepage. If we call for 2 or 3 pages (and
both the stack and several slabs used in process creation are such, at
least with the debug options I had), it assumed it's being called for
stock and just retried without reclaiming.

Fix that by passing down a minsize argument in addition to the csize.

And what to do about that (csize == PAGE_SIZE && ret) retry? If it's
needed at all (and presumably is since it's there, perhaps to handle
races), then it should be extended to more than PAGE_SIZE, yet how far?
And should there be a retry count limit, of what? For now retry up to
COSTLY_ORDER (as page_alloc.c does) and make sure not to do it if
__GFP_NORETRY.

[v4: fixed nr pages calculation pointed out by Christoph Lameter]

Signed-off-by: Suleiman Souhlal <suleiman@google.com>
Signed-off-by: Glauber Costa <glommer@parallels.com>
Acked-by: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>
Acked-by: Michal Hocko <mhocko@suse.cz>
Acked-by: Johannes Weiner <hannes@cmpxchg.org>
CC: Tejun Heo <tj@kernel.org>
---
mm/memcontrol.c | 16 +++++++++-------
1 file changed, 9 insertions(+), 7 deletions(-)

diff --git a/mm/memcontrol.c b/mm/memcontrol.c
index 47cb019..7a9652a 100644
--- a/mm/memcontrol.c
+++ b/mm/memcontrol.c
@@ -2226,7 +2226,8 @@ enum {
};

static int mem_cgroup_do_charge(struct mem_cgroup *memcg, gfp_t gfp_mask,
- unsigned int nr_pages, bool oom_check)
+ unsigned int nr_pages, unsigned int min_pages,
+ bool oom_check)
{
unsigned long csize = nr_pages * PAGE_SIZE;
struct mem_cgroup *mem_over_limit;

```
@@ -2249,18 +2250,18 @@ static int mem_cgroup_do_charge(struct mem_cgroup *memcg,
gfp_t gfp_mask,
  } else
   mem_over_limit = mem_cgroup_from_res_counter(fail_res, res);
  /*
-  * nr_pages can be either a huge page (HPAGE_PMD_NR), a batch
-  * of regular pages (CHARGE_BATCH), or a single regular page (1).
-  *
   * Never reclaim on behalf of optional batching, retry with a
   * single page instead.
   */
- if (nr_pages == CHARGE_BATCH)
+ if (nr_pages > min_pages)
   return CHARGE_RETRY;

  if (!(gfp_mask & __GFP_WAIT))
   return CHARGE_WOULDBLOCK;

+ if (gfp_mask & __GFP_NORETRY)
+  return CHARGE_NOMEM;
+
  ret = mem_cgroup_reclaim(mem_over_limit, gfp_mask, flags);
  if (mem_cgroup_margin(mem_over_limit) >= nr_pages)
   return CHARGE_RETRY;
@@ -2273,7 +2274,7 @@ static int mem_cgroup_do_charge(struct mem_cgroup *memcg, gfp_t
gfp_mask,
   * unlikely to succeed so close to the limit, and we fall back
   * to regular pages anyway in case of failure.
   */
- if (nr_pages == 1 && ret)
+ if (nr_pages <= (1 << PAGE_ALLOC_COSTLY_ORDER) && ret)
   return CHARGE_RETRY;

  /*
@@ -2408,7 +2409,8 @@ again:
    nr_oom_retries = MEM_CGROUP_RECLAIM_RETRIES;
   }

-  ret = mem_cgroup_do_charge(memcg, gfp_mask, batch, oom_check);
+  ret = mem_cgroup_do_charge(memcg, gfp_mask, batch, nr_pages,
+      oom_check);
   switch (ret) {
   case CHARGE_OK:
    break;
--
1.7.11.7
```