
Subject: Experimental OpenVZ on Debian Wheezy (kernel 3.2)

Posted by [dash](#) on Tue, 11 Jun 2013 14:13:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

There is experimental support for non OpenVZ kernels since vzctl 4.0.

I have converted vzctl-core (4.3.1-1), vzctl (4.3.1-1) and vzquota (3.1-1) with alien from rpm to deb.

I have added cgroup_enable=memory swapaccount=1 to the kernel's command line.

Even after tinkering with some other settings I still can't get further as:

```
# vzctl start 101
Directory /proc/vz not found, assuming non-OpenVZ kernel
Starting container...
Mounting root: /vz/root/101 /vz/private/101
Container is mounted
Failed to set limits for TCPbuffer (Cgroup, requested group parameter does not exist)
Failed to set limits for Kernel Memory (Cgroup, requested group parameter does not exist)
WARNING: Running container unprivileged. USER_NS not supported, or runtime disabled
Setting iptables mask 0x000017bf
Setting features mask 0000000000000001/0000000000000001
Running container script: /etc/vz/dists/scripts/debian-add_ip.sh
Running container script: /etc/vz/dists/scripts/prestart.sh
Container start failed (try to check kernel messages, e.g. "dmesg | tail")
Running: /usr/sbin/vzquota stat 101 -f
Container is unmounted
```

My assumption is that one of the newer kernels would solve the-container-is-not-starting problem.

The container config is based on the shipped /etc/sysconfig/vz-scripts/ve-basic.conf-sample.

I would like to find out which one of the cgroup's parameter is missing. So, if I can remove the corresponding limit from the config then the container should theoretically start.

If I set the following parameters

```
TCPSNDBUF="0:0"
TCPRCVBUF="0:0"
```

then the message regarding the TCPbuffer doesn't come up but I'm really unsure what the values

means here or even they do make any sense.

Please help me, and please focus on the question and not on the other ways to use OpenVZ on Debian 3.2.