Subject: [PATCH] reiserfs: add missing D-cache flushing
Posted by Alexey Dobriyan on Tue, 14 Nov 2006 16:36:35 GMT
View Forum Message <> Reply to Message

Looks like, reiserfs_prepare_file_region_for_write() doesn't contain several
flush_dcache_page() calls.

With help from Dmitriy Monakhov.

Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>
---

 fs/reiserfs/file.c | 4 ++++
 1 file changed, 4 insertions(+)

```
--- a/fs/reiserfs/file.c
+++ b/fs/reiserfs/file.c
@@ -1043,6 +1043,7 @@ static int reiserfs_prepare_file_region_
   if (from != 0) { /* First page needs to be partially zeroed */
    char *kaddr = kmap_atomic(prepared_pages[0], KM_USER0);
    memset(kaddr, 0, from);
+   flush_dcache_page(prepared_pages[0]);
    kunmap_atomic(kaddr, KM_USER0);
   }
   if (to != PAGE_CACHE_SIZE) { /* Last page needs to be partially zeroed */
@@ -1050,6 +1051,7 @@ static int reiserfs_prepare_file_region_
        kmap_atomic(prepared_pages[num_pages - 1],
      KM_USER0);
    memset(kaddr + to, 0, PAGE_CACHE_SIZE - to);
+   flush_dcache_page(prepared_pages[num_pages - 1]);
    kunmap_atomic(kaddr, KM_USER0);
   }

@@ -1183,6 +1185,7 @@ static int reiserfs_prepare_file_region_
        KM_USER0);
      memset(kaddr + block_start, 0,
            from - block_start);
+     flush_dcache_page(prepared_pages[0]);
      kunmap_atomic(kaddr, KM_USER0);
      set_buffer_uptodate(bh);
     }
@@ -1220,6 +1223,7 @@ static int reiserfs_prepare_file_region_
        [num_pages - 1],
        KM_USER0);
      memset(kaddr + to, 0, block_end - to);
+     flush_dcache_page(prepared_pages[num_pages - 1]);
      kunmap_atomic(kaddr, KM_USER0);
      set_buffer_uptodate(bh);
```

```
}
```