
Subject: Re: Separate logfile and console loglevel
Posted by [Igor Sukhih](#) on Tue, 05 Dec 2006 11:40:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

> On Tuesday den 5. December 2006 11:47, Igor Sukhih wrote:
>

>>
>>> On Thursday den 30. November 2006 14:59, Dmitry Mishin wrote:
>>>

>>>>
>>>>> Separate logfile and console loglevel
>>>>> The separation is implemented as follows
>>>>>
>>>>> 1: split --quite and --verbose from LOG_LEVEL
>>>>> console loglevel is 0 as default
>>>>>

>>>> This patch make sense.

>>>>
>>> I worked on the patch, made --verbose accept argument (--verbose=<int>)
>>> Added new parameter VERBOSE=<int> to /etc/vz/vz.conf. Default is 1 if
>>> unset. --verbose alone increments by 1
>>>

>>>>> 2: Make messages more quiet by default
>>>>> logger(0,...) -> logger(1, ...)
>>>>>

>>>>> 3: Make logfile more verbose by default
>>>>> LOG_LEVEL=2
>>>>>

>>>> Why do you need them? For me, it is convinient to see at the VE start,
>>>> which IP it has. It is better, than additional `vzlist` later.

>>>>
>>> If I use a script to start 10 VEs, it would be nice to see only partial
>>> info. I could do that with --verbose=0. If one fails I can use
>>> --verbose=2 What do you think about the output below?

>>>
>> I'm Ok with it the only problem the --verbose option already released
>> and this is can break already worked scripts.

>>
>
> --verbose still works. It increments current verbose by 1.
> If I run:
> vzctl --verbose=0 --verbose --verbose start 1010
> verbose will be 2 (0 + 1 + 1)

>

If I correctly understand you will process --verbose and --verbose=0 the same way?

So 'vzctl --verbose ' will work as well?

>

>>> Regards,

>>>

>>> Ps.

>>> vzquota, /etc/vz/dists/scripts/none and vps-net_add/vps-net_del are just

>>> "exit 0"

>>>

>> They do exit with error in place error happened.

>>

> I was unclear. My scripts only contains "exit 0".

> I don't know if the standard scripts make any output by default.

>

There only error output by default, look at error() function.

Prints error message and exits

Parameters:

\$1 - error message

\$2 - exit code

Example of usage:

error "Fatal error" 1

function error()

--

Igor.
