Subject: NFS inside VE
Posted by Alex Prinsier on Sat, 06 Jan 2007 10:55:21 GMT
View Forum Message <> Reply to Message

I'm having trouble getting nfs to work inside a VE.

I think I've set it up correctly... Does anyone see a big mistake in my configuration here?

```
# cat /etc/exports
/data   10.1.1.0/24(rw,no_root_squash)

# ps aux  (only copied the relevant daemons)
USER       PID %CPU %MEM    VSZ  RSS TTY      STAT START    TIME COMMAND
daemon   24471  0.0  0.0   3040  452 ?        Ss   Jan05   0:00 /sbin/portmap
root      7673  0.0  0.0   3640  544 ?        Ss   Jan05   0:00
/usr/sbin/rpc.nfsd -r
root      7675  0.0  0.0   3096  680 ?        S    Jan05   0:00
/usr/sbin/rpc.mountd -r
```

The ip of that machine is 10.1.1.2 (and I'm executing the mount on the same machine).

```
# mount 10.1.1.2:/data /mnt
mount: 10.1.1.2:/data failed, reason given by server: Permission denied
```

I get these lines in syslog:

```
Jan  6 10:49:03 fs mountd[7675]: NFS mount of /data attempted from 10.1.1.2
Jan  6 10:49:03 fs mountd[7675]: Unauthorized access by NFS client
10.1.1.2.
Jan  6 10:49:03 fs mountd[7675]: Blocked attempt of 10.1.1.2 to mount /data
```

```
# rpcinfo -p 10.1.1.2
   program vers proto   port
    100000    2   tcp    111  portmapper
    100000    2   udp    111  portmapper
    100003    2   udp   2049  nfs
    100003    2   tcp   2049  nfs
    100005    1   udp    644  mountd
    100005    2   udp    644  mountd
    100005    1   tcp    647  mountd
    100005    2   tcp    647  mountd
```

Here is an strace of the mount:

```
# strace mount 10.1.1.2:/data /mnt
execve("/bin/mount", ["mount", "10.1.1.2:/data", "/mnt"], [/* 11 vars
*/]) = 0
uname({sys="Linux", node="fs.internal.ejibe.net", ...}) = 0
brk(0)                                  = 0x856d000
```

```
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0xb7fed000
access("/etc/ld.so.nohwcap", F_OK)      = -1 ENOENT (No such file or
directory)
open("/etc/ld.so.preload", O_RDONLY)    = -1 ENOENT (No such file or
directory)
open("/etc/ld.so.cache", O_RDONLY)      = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=7889, ...}) = 0
old_mmap(NULL, 7889, PROT_READ, MAP_PRIVATE, 3, 0) = 0xb7feb000
close(3)                                = 0
access("/etc/ld.so.nohwcap", F_OK)      = -1 ENOENT (No such file or
directory)
open("/lib/libblkid.so.1", O_RDONLY)    = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0P\35\0\000"...,
512) = 512
fstat64(3, {st_mode=S_IFREG|0644, st_size=27548, ...}) = 0
old_mmap(NULL, 26520, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0xcef000
old_mmap(0xcf5000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x6000) = 0xcf5000
close(3)                                = 0
access("/etc/ld.so.nohwcap", F_OK)      = -1 ENOENT (No such file or
directory)
open("/lib/libuuid.so.1", O_RDONLY)     = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\240\f\0"...,
512) = 512
fstat64(3, {st_mode=S_IFREG|0644, st_size=9232, ...}) = 0
old_mmap(NULL, 12260, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x217000
old_mmap(0x219000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x1000) = 0x219000
close(3)                                = 0
access("/etc/ld.so.nohwcap", F_OK)      = -1 ENOENT (No such file or
directory)
open("/lib/tls/libc.so.6", O_RDONLY)    = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0`Z\1\000"...,
512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1254660, ...}) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0xb7fea000
old_mmap(NULL, 1264972, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x21a000
old_mmap(0x344000, 36864, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED,
3, 0x129000) = 0x344000
old_mmap(0x34d000, 7500, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x34d000
close(3)                                = 0
set_thread_area({entry_number:-1 -> 6, base_addr:0xb7fea860,
limit:1048575, seg_32bit:1, contents:0, read_exec_only:0,
limit_in_pages:1, seg_not_present:0, useable:1}) = 0
munmap(0xb7feb000, 7889)                = 0
```

```
brk(0)                          = 0x856d000
brk(0x858e000)                  = 0x858e000
brk(0)                          = 0x858e000
umask(022)                      = 022
open("/dev/null", O_RDWR|O_LARGEFILE)   = 3
close(3)                        = 0
getuid32()                      = 0
geteuid32()                     = 0
getgid32()                      = 0
getgid32()                      = 0
prctl(0x3, 0x20, 0x856d030, 0xcf5658, 0xcf5658) = 1
open("/etc/blkid.tab", O_RDONLY)        = -1 ENOENT (No such file or
directory)
getuid32()                      = 0
geteuid32()                     = 0
lstat64("/etc/mtab", {st_mode=S_IFLNK|0777, st_size=12, ...}) = 0
stat64("10.1.1.2:/data", 0xbffa0df0)    = -1 ENOENT (No such file or
directory)
stat64("/sbin/mount.nfs", 0xbffa0c60)   = -1 ENOENT (No such file or
directory)
uname({sys="Linux", node="fs.internal.ejibe.net", ...}) = 0
time(NULL)                      = 1168080828
socket(PF_INET, SOCK_STREAM, IPPROTO_TCP) = 3
getpid()                        = 14303
bind(3, {sa_family=AF_INET, sin_port=htons(911),
sin_addr=inet_addr("0.0.0.0")}, 16) = 0
connect(3, {sa_family=AF_INET, sin_port=htons(111),
sin_addr=inet_addr("10.1.1.2")}, 16) = 0
gettimeofday({1168080828, 691188}, NULL) = 0
write(3, "\200\0\0(\0236\212\302\0\0\0\0\0\0\2\0\1\206\240\0\0"...,
44) = 44
poll([{fd=3, events=POLLIN, revents=POLLIN}], 1, 60000) = 1
read(3, "\200\0\0\274\0236\212\302\0\0\0\1\0\0\0\0\0\0\0\0\0\0\0"...,
500) = 192
close(3)                        = 0
socket(PF_INET, SOCK_DGRAM, IPPROTO_UDP) = 3
bind(3, {sa_family=AF_INET, sin_port=htons(912),
sin_addr=inet_addr("0.0.0.0")}, 16) = 0
ioctl(3, FIONBIO, [1])          = 0
setsockopt(3, SOL_IP, IP_RECVERR, [1], 4) = 0
uname({sys="Linux", node="fs.internal.ejibe.net", ...}) = 0
geteuid32()                     = 0
getegid32()                     = 0
getgroups32(32, [0])            = 1
gettimeofday({1168080828, 693409}, NULL) = 0
sendto(3, "1\202\312\204\0\0\0\0\0\0\2\0\1\206\245\0\0\0\2\0\0\0"...,
100, 0, {sa_family=AF_INET, sin_port=htons(644),
sin_addr=inet_addr("10.1.1.2")}, 16) = 100
```

```
poll([{fd=3, events=POLLIN, revents=POLLIN}], 1, 3000) = 1
recvfrom(3,
"1\202\312\204\0\0\0\1\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"..., 8800, 0,
{sa_family=AF_INET, sin_port=htons(644),
sin_addr=inet_addr("10.1.1.2")}, [16]) = 28
write(2, "mount: 10.1.1.2:/data failed, re"..., 72mount: 10.1.1.2:/data
failed, reason given by server: Permission denied
) = 72
close(3)                        = 0
close(3)                        = -1 EBADF (Bad file descriptor)
exit_group(32)                  = ?
```