Subject: vztcl runscript and keep the same env variables?
Posted by Benjamin Henrion on Sun, 25 Sep 2011 11:40:23 GMT
View Forum Message <> Reply to Message

Hi,

In a simple bash script named "test.sh", I used to call another shell
script "part1.sh" keeping the same Env variables like this:

$head -n 1 test.sh
. ./part1.sh

Now, I would like to do the same with vzctl runscript:

$head -n 1 test.sh
vzctl runscript 1110 part1.sh

How do I do that?

Best,

--
Benjamin Henrion <bhenrion at ffii.org>
FFII Brussels - +32-484-566109 - +32-2-4148403
"In July 2005, after several failed attempts to legalise software
patents in Europe, the patent establishment changed its strategy.
Instead of explicitly seeking to sanction the patentability of
software, they are now seeking to create a central European patent
court, which would establish and enforce patentability rules in their
favor, without any possibility of correction by competing courts or
democratically elected legislators."

Subject: Re: vztcl runscript and keep the same env variables?
Posted by samiam on Sun, 25 Sep 2011 16:56:47 GMT
View Forum Message <> Reply to Message

> In a simple bash script named "test.sh", I used to call another shell
> script "part1.sh" keeping the same Env variables like this:
>
> $head -n 1 test.sh
> . ./part1.sh
>
> Now, I would like to do the same with vzctl runscript:
>
> $head -n 1 test.sh
> vzctl runscript 1110 part1.sh

```
echo '#!/bin/bash' > tmp.sh
env | awk -F= '{print $1 "=\"" $2 "\""}' >> tmp.sh
cat part1.sh >> tmp.sh
vzctl runscript 1110 tmp.sh
rm tmp.sh
```

Escaping quotes in environmental variables or using mktemp is left as an exercise to the reader.

- Sam

Subject: Re: vztcl runscript and keep the same env variables?
Posted by samiam on Sun, 25 Sep 2011 17:30:53 GMT
View Forum Message <> Reply to Message

> env | awk -F= '{print "export " $1 "=\"" $2 "\""}' >> tmp.sh

Works even better :)
