Subject: [PATCH v2 0/5] NFS: create blocklayout pipe per network namesapce context
Posted by Stanislav Kinsbursky on Tue, 10 Jan 2012 13:04:07 GMT
View Forum Message <> Reply to Message

This patch set was created in context of clone of git
branch: git://git.linux-nfs.org/projects/trondmy/nfs-2.6.git.
tag: v3.2

v2:
1) rebased on tag v3.2

This patch set depends on previous patch sets titled:
1) "SUNRPC: initial part of making pipefs work in net ns"
2) "SUNPRC: cleanup PipeFS for network-namespace-aware users"
3) "SUNRPC: make RPC clients use network-namespace-aware PipeFS routines"
4) "NFS: create clients and IDMAP pipes per network namespace"

This patch set is the final part of making SUNRPC PipeFS and it's users work in
network namespace context.

The following series consists of:

Stanislav Kinsbursky (5):
    NFS: handle blocklayout pipe PipeFS dentry by network namespace aware routines
    NFS: blocklayout pipe creation per network namespace context introduced
    NFS: blocklayout PipeFS notifier introduced
    NFS: remove RPC PipeFS mount point reference from blocklayout routines
    SUNRPC: kernel PipeFS mount point creation routines removed

 fs/nfs/blocklayout/blocklayout.c | 160 ++++++++++++++++++++++++++++++-------
 fs/nfs/blocklayout/blocklayout.h | 3 -
 fs/nfs/blocklayout/blocklayoutdev.c | 5 +
 fs/nfs/blocklayout/blocklayoutdm.c | 7 +-
 fs/nfs/inode.c | 1
 fs/nfs/netns.h | 1
 include/linux/sunrpc/rpc_pipe_fs.h | 2
 net/sunrpc/rpc_pipe.c | 21 -----
 8 files changed, 139 insertions(+), 61 deletions(-)

--
Signature