Subject: Netstat on Deb ovz vs Deb Proxmox
Posted by Christian Blaich on Mon, 18 Jun 2012 16:18:02 GMT
View Forum Message <> Reply to Message

-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1

Hi guys,

i'm working on a monitoring solution for my hardwarenodes.
Hosts A with Debian Squeeze and linux-image-2.6.32-5-openvz-amd64 from
the Debian Repository and Hosts B Debian Squeeze with Proxmox
2.6.32-12-pve from the Proxmoxrepo.
Both working with ovz Containers. When i'm trying to check netstat on
Hosts A i see the Connections from the Hardwarenode, such as ntp. Hosts
B (Proxmox) tells me the whole Connectiontree including every VM connection.
That result is bad for my checks and i don't wanna write seperate checks
for A & B.
Any ideas ?

-----BEGIN PGP SIGNATURE-----
Version: GnuPG/MacGPG2 v2.0.17 (Darwin)
Comment: GPGTools - http://gpgtools.org
Comment: Using GnuPG with Mozilla - http://enigmail.mozdev.org/

iQEcBAEBAgAGBQJP31S5AAoJENzPm0AOTN5bJzgIAJPEnA0oUaBIDWwlpkT1 OrCv
HKlAKDFiqgkKZ7rVvDyxm7hgqRJNvgnq76c/RbF9dOXt71XiP10EtHGamJWs j1XN
72Sqru6AhLCUakk1hqaNXITTs963VGXx9ZqwtghXct5yEFte1nYEgzCvUbMb q8r3
vpkCb1rViomKtykCZGPMDiHd08K91dcWEEtqGDr1is3WDw2rLX7VxThpM0DD Un6M
o2UZCcDQxW2EI3FbhRwEAFywjgWaMeh+u4tWIcP3mOhvtt2ANcKjlso2c7Kb Vhxv
us2Y5YXuawj1BGJ0qfW1s8KdqxfopSYJ4yVyKlFyTB+KADibsEo6NT7BBs4l nOA=
=g/TT
-----END PGP SIGNATURE-----

Subject: Re: Netstat on Deb ovz vs Deb Proxmox
Posted by Joseph Hauptmann on Tue, 19 Jun 2012 08:39:40 GMT
View Forum Message <> Reply to Message

Hi OpenVZ-Community, Hi Christian,

I noticed the same "problem" with the 2.6.32 kernels. Interestingly it
only seems to happen on my rpm-based Kernels from the OpenVZ-Repo. The
kernels I patched and compiled myself don't seem to behave that way.

Also, not all processes that open ports seem to be visible via netstat
on the hw-node. Here the difference in behaviour between munin and apache2:

```
[root@srv05 ~]# vzctl exec 512 "netstat -tulpen | grep 4949"
tcp        0      0 0.0.0.0:4949            0.0.0.0:*
LISTEN      0          23963289    14168/munin-node
[root@srv05 ~]# vzctl exec 510 "netstat -tulpen | grep 4949"
tcp        0      0 0.0.0.0:4949            0.0.0.0:*
LISTEN      0          154512328   31520/munin-node
[root@srv05 ~]# netstat -tulpen|grep 4949
tcp        0      0 0.0.0.0:4949
0.0.0.0:*                   LISTEN      0          56159312
652391/munin-node
[root@srv05 ~]# netstat -tulpen|grep :80
tcp        0      0 0.0.0.0:80
0.0.0.0:*                   LISTEN      0          547379989
191426/apache2
tcp        0      0 :::80
:::*                        LISTEN      0          28979
10656/httpd
```

I only use venet-based networking on all my nodes.

Am 2012-06-18 18:18, schrieb Christian Blaich:
> Hi guys,
>
> i'm working on a monitoring solution for my hardwarenodes.
> Hosts A with Debian Squeeze and linux-image-2.6.32-5-openvz-amd64 from
> the Debian Repository and Hosts B Debian Squeeze with Proxmox
> 2.6.32-12-pve from the Proxmoxrepo.
> Both working with ovz Containers. When i'm trying to check netstat on
> Hosts A i see the Connections from the Hardwarenode, such as ntp. Hosts
> B (Proxmox) tells me the whole Connectiontree including every VM
connection.
> That result is bad for my checks and i don't wanna write seperate checks
> for A & B.
> Any ideas ?
>
>
>
>
>
>
--
Joseph Hauptmann

/digiconcept/ - GmbH.
1080 Wien
Blindengasse 52/1

Tel. +43 1 218 0 212 - 24
Fax +43 1 218 0 212 - 10