Subject: qmailtoaster and vps dependencies
Posted by victorskl on Sun, 19 Nov 2006 06:56:12 GMT
View Forum Message <> Reply to Message

Dear all,

i wanna give a try qmailtoaster on vps according to their wiki guide. But i found out that there is some dependencies issue just after first installation of deps sh script.

the shell script is as follow. any idea why i cant install on vps. i try on centos template vps. i will try with fedora 5 template vps soon.

```
#!/bin/sh
#
# CentOS 4.3 dependencies for basic install
#
#
# Removes sendmail and adds all deps
#
# Removes openssl and installs it again because
# it conflicts with it's own files (?)
#

rpm --import /usr/share/doc/centos-release-4/RPM*

yum -y remove sendmail
rpm -e --nodeps openssl

yum -y install autoconf automake automake17 bzip2 bzip2-devel curl curl-devel expect
expect-devel gcc gcc-c++ gcc-g77 gdbm
gdbm-devel gmp gmp-devel httpd httpd-devel httpd-manual httpd-suexec krb5-auth-dialog
krb5-devel krb5-libs krb5-workstation
libgcc libidn libidn-devel libtool mysql mysql-bench mysql-devel mysql-server mrtg ntp openssh
openssh-clients
openssh-askpass openssh-server openssl openssl-devel pcre pcre-devel perl-Digest-HMAC
perl-Digest-SHA1 perl-Net-DNS
perl-Time-HiRes php php-ldap php-mysql php-pear redhat-rpm-config rpm-build rpm-devel
rpm-libs rpm-python sed setup
setuptool stunnel system-config-date which
```

thanks

Subject: Re: qmailtoaster and vps dependencies
Posted by rickb on Sun, 19 Nov 2006 08:46:31 GMT
View Forum Message <> Reply to Message

Whats the specific error you get? Basically theres very little difference between a CD installed distro and the distro templates in the openvz archive. So, its likely that its not a vz problem specifically. Paste us the error you get when you run that script/rpm commands.

Rick

Subject: Re: qmailtoaster and vps dependencies
Posted by hossi on Tue, 20 Feb 2007 07:58:35 GMT
View Forum Message <> Reply to Message

Hello every body,

I have installed Qmail Toaster on my Fedora core4 completely. Every thing seems to work. I want to restrict or limit the access of each subscriber to communicate to others. What program should I use? I tried Maildrop, but it doesn't seem to be functioning. Or I don't know how to make Qmail to use maildrop as the delivery program. I put "| /usr/bin/maildrop " in the file "qmail-default" in the home directory of my virtual account, but it didn't work. Am I on the right track? or ...
I appreciate anybody helping to solve this problem.

Hossi

Subject: Re: qmailtoaster and vps dependencies
Posted by victorskl on Thu, 22 Feb 2007 12:40:37 GMT
View Forum Message <> Reply to Message

Oh.. you get it through. That's good. Since my try is not success at first attempt, i used cyrus and webcyradm that work charm.

So you use FC4 template. Can i check with you, did you follow to install it by Qmail Toaster installation instruction?

Thanks.
