Subject: LTP: serge2 hostname
Posted by Alexey Dobriyan on Wed, 23 May 2007 14:13:55 GMT
View Forum Message <> Reply to Message

I ran ltp-full-20070430 and utstest.c forgot to restore original
hostname from serge2. ;-)

Subject: Re: LTP: serge2 hostname
Posted by serue on Wed, 23 May 2007 14:49:44 GMT
View Forum Message <> Reply to Message

Quoting Alexey Dobriyan (adobriyan@sw.ru):
> I ran ltp-full-20070430 and utstest.c forgot to restore original
> hostname from serge2. ;-)

Oh that's just me taking over the world, one workstation at a time.

Hopefully this simple obvious silly workaround fixes it?

It should also fix 'make no_ltp' which I hadn't realized was broken
until I just tried to test the hostname fix...

thanks for spotting that.

-serge

```
Only in  ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone: libclone.a
Only in  ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone: libclone.o
diff -ur  ltp-full-20070430/testcases/kernel/containers/utsname/Makefi le
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/Makefile
---  ltp-full-20070430/testcases/kernel/containers/utsname/Makefi le 2007-04-26
13:02:51.000000000 +0200
+++  ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/Makefile 2007-05-23
16:48:26.000000000 +0200
@@ -4,8 +4,9 @@
 LDLIBS += -L../../../../lib -L../libclone ../libclone/libclone.a -lltp

 SRCS    = $(wildcard *.c)
+NOLTPSRCS = utstest.c
 TARGETS = $(patsubst %.c,%,$(SRCS))
-NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(SRCS))
+NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(NOLTPSRCS))

 %_noltp : %.c
  $(CC) -g -DNO_LTP -o $@ $< ../libclone/libclone.a
diff -ur  ltp-full-20070430/testcases/kernel/containers/utsname/runtes ts_noltp.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runtests_noltp.sh
```

```
---  ltp-full-20070430/testcases/kernel/containers/utsname/runtes ts_noltp.sh 2007-04-26
13:02:51.000000000 +0200
+++  ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn
ame/runtests_noltp.sh 2007-05-23 16:44:32.000000000 +0200
@@ -1,5 +1,6 @@
 #!/bin/sh

+oldhostname=`hostname`
 exit_code=0
 echo "unshare tests"
 for i in `seq 1 5`; do
@@ -17,4 +18,5 @@
   exit_code=$?
  fi
 done
+hostname "$oldhostname"
 exit $exit_code
diff -ur  ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runutstest.sh
---  ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh 2007-04-26
13:02:51.000000000 +0200
+++  ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runutstest.sh 2007-05-23
16:44:37.000000000 +0200
@@ -1,5 +1,6 @@
 #!/bin/sh

+oldhostname=`hostname`
 echo "unshare tests"
 for i in `seq 1 5`; do
  echo "test $i (unshare)"
@@ -10,3 +11,4 @@
  echo "test $i (clone)"
  utstest clone $i
 done
+hostname "$oldhostname"
Only in  ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame: utstest_noltp
```

Subject: Re: [LTP] LTP: serge2 hostname
Posted by Subrata Modak1 on Thu, 24 May 2007 07:08:26 GMT
View Forum Message <> Reply to Message

Taken Care.

Regards & Thanks--
Subrata Modak,
==========
==========

"Serge E. Hallyn"
<serue@us.ibm.com
>
Sent by:
ltp-list-bounces@
lists.sourceforge
.net

To
Alexey Dobriyan <adobriyan@sw.ru>
cc
ltp-list@lists.sourceforge.net,
devel@openvz.org
Subject
Re: [LTP] LTP: serge2 hostname
05/23/07 08:19 PM

Quoting Alexey Dobriyan (adobriyan@sw.ru):
> I ran ltp-full-20070430 and utstest.c forgot to restore original
> hostname from serge2. ;-)

Oh that's just me taking over the world, one workstation at a time.

Hopefully this simple obvious silly workaround fixes it?

It should also fix 'make no_ltp' which I hadn't realized was broken
until I just tried to test the hostname fix...

thanks for spotting that.

-serge

Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone:
libclone.a
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone:
libclone.o
diff -ur ltp-full-20070430/testcases/kernel/containers/utsname/Makefi le
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/Makefile
--- ltp-full-20070430/testcases/kernel/containers/utsname/Makefi le
2007-04-26 13:02:51.000000000 +0200
+++
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/Makefile

```
       2007-05-23 16:48:26.000000000 +0200
@@ -4,8 +4,9 @@
 LDLIBS += -L../../../../lib -L../libclone ../libclone/libclone.a -lltp

 SRCS    = $(wildcard *.c)
+NOLTPSRCS = utstest.c
 TARGETS = $(patsubst %.c,%,$(SRCS))
-NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(SRCS))
+NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(NOLTPSRCS))

 %_noltp : %.c
            $(CC) -g -DNO_LTP -o $@ $< ../libclone/libclone.a
diff -ur
 ltp-full-20070430/testcases/kernel/containers/utsname/runtes ts_noltp.sh
 ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runtests_noltp.sh

---  ltp-full-20070430/testcases/kernel/containers/utsname/runtes ts_noltp.sh
       2007-04-26 13:02:51.000000000 +0200
+++
 ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runtests_noltp.sh
            2007-05-23 16:44:32.000000000 +0200
@@ -1,5 +1,6 @@
 #!/bin/sh

+oldhostname=`hostname`
 exit_code=0
 echo "unshare tests"
 for i in `seq 1 5`; do
@@ -17,4 +18,5 @@
                        exit_code=$?
            fi
 done
+hostname "$oldhostname"
 exit $exit_code
diff -ur
 ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh
 ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runutstest.sh

---  ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh
 2007-04-26 13:02:51.000000000 +0200
+++
 ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame/runutstest.sh
            2007-05-23 16:44:37.000000000 +0200
@@ -1,5 +1,6 @@
 #!/bin/sh

+oldhostname=`hostname`
 echo "unshare tests"
```

```
 for i in `seq 1 5`; do
         echo "test $i (unshare)"
@@ -10,3 +11,4 @@
         echo "test $i (clone)"
         utstest clone $i
 done
+hostname "$oldhostname"
Only in  ltp-full-20070430-fixserge2/testcases/kernel/containers/utsn ame:
utstest_noltp
```

This SF.net email is sponsored by DB2 Express
Download DB2 Express C - the FREE version of DB2 express and take
control of your XML. No limits. Just data. Click to get it now.
http://sourceforge.net/powerbar/db2/

_____

Ltp-list mailing list
Ltp-list@lists.sourceforge.net
https://lists.sourceforge.net/lists/listinfo/ltp-list

Subject: Re: LTP: serge2 hostname
Posted by Alexey Dobriyan on Thu, 24 May 2007 10:08:05 GMT
View Forum Message <> Reply to Message

On Wed, May 23, 2007 at 09:49:44AM -0500, Serge E. Hallyn wrote:
> Quoting Alexey Dobriyan (adobriyan@sw.ru):
> > I ran ltp-full-20070430 and utstest.c forgot to restore original
> > hostname from serge2. ;-)
>
> Oh that's just me taking over the world, one workstation at a time.
>
> Hopefully this simple obvious silly workaround fixes it?

Thanks, it's all fine now.
