
Subject: trouble with veth device in combination with long veid

Posted by [Nils Domrose](#) on Wed, 06 Jun 2007 15:14:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

we are facing a problem with veth device in combination with long veids.
if we configure a veth device as described in the wiki, we are unable
to start that VE with the following error:

```
xnetadm:/etc/vz/conf# vzctl start 249104
Starting VE ...
VE is mounted
Setting CPU units: 23945
Configure meminfo: 655360
Set hostname: vz-netnagios
File resolv.conf was modified
Configure veth devices: veth104.0
debug veid 24910 vznetcfg
debug veid 24910 vznetaddroute
/usr/sbin/vznetaddroute: line 6: /etc/vz/conf/24910.conf: No such
file or directory
According to /etc/vz/conf/24910.conf VE has no veth IPs configured.
/usr/sbin/vznetcfg exited with error
VE start failed
Stopping VE ...
VE was stopped
VE is unmounted
```

Note that we are echoing the \$VEID in vznetcfg and vznetaddroute for
debugging reasons and we noticed that the last character is cut off.
This is also the reason why the scripts fail. We have not yet figured
out if vznetcfg is called by vzctl directly.

This does not happen if we use a shorter veid like 104.

Maybe someone has an idea what is causing the issue.

Here is the vzctl log output.

```
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Starting VE ...
2007-06-06T16:23:28+0200 vzctl : VE 249104 : VE is mounted
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Setting CPU units: 23945
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Configure meminfo: 655360
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Set hostname: vz-netnagios
```

```
2007-06-06T16:23:28+0200 vzctl : VE 249104 : File resolv.conf was
modified
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Configure veth devices:
veth104.0
2007-06-06T16:23:28+0200 vzctl : VE 249104 : /usr/sbin/vznetcfg
exited with error
2007-06-06T16:23:28+0200 vzctl : VE 249104 : VE start failed
2007-06-06T16:23:28+0200 vzctl : VE 249104 : Stopping VE ...
2007-06-06T16:23:28+0200 vzctl : VE 249104 : VE was stopped
2007-06-06T16:23:29+0200 vzctl : VE 249104 : VE is unmounted
```

kernel version:

```
Linux xnetadm 2.6.18-028stab033.1-ovz-smp #1 SMP Thu May 31 10:29:27
CEST 2007 x86_64 GNU/Linux
```

vzctl version:

```
xnetadm:/usr/lib/vzctl/scripts# vzctl --version
vzctl version 3.0.16-5dso1
```

Nils

Subject: Re: trouble with veth device in combination with long veid
Posted by [kfh](#) on Thu, 07 Jun 2007 07:45:59 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Wednesday den 6. June 2007 17:14:57 Nils Domrose wrote:

```
> Hi,
>
> we are facing a problem with veth device in combination with long veids.
> if we configure a veth device as described in the wiki, we are unable
> to start that VE with the following error:
>
```

In veth.c a buffer with length 11 is allocated.
The buffer is used as follows:
`snprintf(buf, sizeof(buf), "VEID=%d", veid);`

As 6 characters are used for static content (VEID= + '\0'), only 5 characters are left. Your VEID (249104) is 6 characters long.

Apply the following patch, and you should be running.
(An alternative is to limit your VEID in the range 100 to <= 99999)

```
--- a/src/lib/veth.c
+++ b/src/lib/veth.c
@@ -90,7 +90,7 @@ static int veth_dev_remove(vps_handler *h, envid_t veid, veth_dev *dev)
static int run_vznetcfg(envid_t veid, veth_dev *dev)
{
int ret;
- char buf[11];
+ char buf[12];
char *argv[] = {VZNETCFG, "init", "veth", NULL, NULL};
char *env[2];
```

(Last line is empty)

Regards,

Subject: Re: trouble with veth device in combination with long veid
Posted by [dev](#) on Thu, 07 Jun 2007 09:32:39 GMT
[View Forum Message](#) <> [Reply to Message](#)

> On Wednesday den 6. June 2007 17:14:57 Nils Domrose wrote:
>
>>Hi,
>>
>>we are facing a problem with veth device in combination with long veids.
>>if we configure a veth device as described in the wiki, we are unable
>>to start that VE with the following error:
>>
>
>
> In veth.c a buffer with length 11 is allocated.
> The buffer is used as follows:
> snprintf(buf, sizeof(buf), "VEID=%d", veid);
>
> As 6 characters are used for static content (VEID= + '\0'), only 5
> characters are left. Your VEID (249104) is 6 characters long.
>
> Apply the following patch, and you should be running.
> (An alternative is to limit your VEID in the range 100 to <= 99999)
>
>
> --- a/src/lib/veth.c
> +++ b/src/lib/veth.c
> @@ -90,7 +90,7 @@ static int veth_dev_remove(vps_handler *h, envid_t veid, veth_dev *dev)
> static int run_vznetcfg(envid_t veid, veth_dev *dev)
> {

```
> int ret;
> - char buf[11];
> + char buf[12];
> char *argv[] = {VZNETCFG, "init", "veth", NULL, NULL};
> char *env[2];
>
> (Last line is empty)
```

In kernel if name is limited to 16 bytes, i.e. to 15 chars (plus zero).
4 chars for "veth", so 11 chars for number. VEID is int, so limited
to 2^32, which is no more than 10 chars length. So everything should
be fine except this silly bug in vzctl.

Why have you chosen 12 instead of 11?
AFAICS it should be sizeof("VEID=") + 10 + 1 (for \0) = 16

Thanks,
Kirill

Subject: Re: trouble with veth device in combination with long veid
Posted by [kfh](#) on Thu, 07 Jun 2007 12:08:26 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Thursday den 7. June 2007 11:32:39 Kirill Korotaev wrote:

```
> > On Wednesday den 6. June 2007 17:14:57 Nils Domrose wrote:
> >>Hi,
> >>
> >>we are facing a problem with veth device in combination with long veids.
> >>if we configure a veth device as described in the wiki, we are unable
> >>to start that VE with the following error:
> >
> > In veth.c a buffer with length 11 is allocated.
> > The buffer is used as follows:
> > snprintf(buf, sizeof(buf), "VEID=%d", veid);
> >
> > As 6 characters are used for static content (VEID= + '\0'), only 5
> > characters are left. Your VEID (249104) is 6 characters long.
> >
> > Apply the following patch, and you should be running.
> > (An alternative is to limit your VEID in the range 100 to <= 99999)
> >
> >
> > --- a/src/lib/veth.c
> > +++ b/src/lib/veth.c
> > @@ -90,7 +90,7 @@ static int veth_dev_remove(vps_handler *h, envid_t
> > veid, veth_dev *dev) static int run_vznetcfg(envid_t veid, veth_dev *dev)
```

```
> > {
> > int ret;
> > - char buf[11];
> > + char buf[12];
> > char *argv[] = {VZNETCFG, "init", "veth", NULL, NULL};
> > char *env[2];
> >
> > (Last line is empty)
>
> In kernel if name is limited to 16 bytes, i.e. to 15 chars (plus zero).
> 4 chars for "veth",
I call my veth interfaces ve${VEID}.0, ve${VEID}.1 ...
So VEID 1234 will have an interface called ve1234.0 in VE0 (eth0 in VE 1234)
```

> so 11 chars for number. VEID is int, so limited
> to 2^{32} , which is no more than 10 chars length. So everything should
> be fine except this silly bug in vzctl.
What if I call my veth interfase abcdefghij\${VEID} ?

(Or do I misunderstand?)

> Why have you chosen 12 instead of 11?
> AFAICS it should be `sizeof("VEID=") + 10 + 1 (for \0) = 16`
I chose 12 because 11 was to small :-)
It was ment as a workaround. 16 must be right.

> Thanks,
> Kirill

Regards,
Kristian.

Subject: Re: trouble with veth device in combination with long veid
Posted by [Thorsten Schifferdeck](#) on Thu, 07 Jun 2007 15:02:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

or export the right VEID from /proc/vz/veth:

```
/proc/vz/veth :
MAC_VE0 veth_dev_on_VE0 mac_dev_VE dev_VE VEID deny
```

Attached a workaround patch, to solve this issue.

Regards,
Thorsten

> On Thursday den 7. June 2007 11:32:39 Kirill Korotaev wrote:

>>> On Wednesday den 6. June 2007 17:14:57 Nils Domrose wrote:

>>>> Hi,

>>>>

>>>> we are facing a problem with veth device in combination with long veids.

>>>> if we configure a veth device as described in the wiki, we are unable

>>>> to start that VE with the following error:

>>> In veth.c a buffer with length 11 is allocated.

>>> The buffer is used as follows:

>>> snprintf(buf, sizeof(buf), "VEID=%d", veid);

>>>

>>> As 6 characters are used for static content (VEID= + '\0'), only 5

>>> characters are left. Your VEID (249104) is 6 characters long.

>>>

>>> Apply the following patch, and you should be running.

>>> (An alternative is to limit your VEID in the range 100 to <= 99999)

>>>

>>>

>>> --- a/src/lib/veth.c

>>> +++ b/src/lib/veth.c

>>> @@ -90,7 +90,7 @@ static int veth_dev_remove(vps_handler *h, envid_t

>>> veid, veth_dev *dev) static int run_vznetcfg(envid_t veid, veth_dev *dev)

>>> {

>>> int ret;

>>> - char buf[11];

>>> + char buf[12];

>>> char *argv[] = {"VZNETCFG", "init", "veth", NULL, NULL};

>>> char *env[2];

>>>

>>> (Last line is empty)

>> In kernel if name is limited to 16 bytes, i.e. to 15 chars (plus zero).

>> 4 chars for "veth",

> I call my veth interfaces ve\${VEID}.0, ve\${VEID}.1 ...

> So VEID 1234 will have an interface called ve1234.0 in VE0 (eth0 in VE 1234)

>

>> so 11 chars for number. VEID is int, so limited

>> to 2^32, which is no more then 10 chars length. So everything should

>> be fine except this silly bug in vzctl.

> What if I call my veth interfase abcdefghij\${VEID} ?

>

> (Or do I misunderstand?)

>

>> Why have you chosen 12 instead of 11?

>> AFAICS it should be sizeof("VEID=") + 10 + 1 (for \0) = 16

> I chose 12 because 11 was to small :-)

> It was ment as a workaround. 16 must be right.
>
>> Thanks,
>> Kirill
>
> Regards,
> Kristian.
>
