Subject: Tweak /proc/ipmi removal
Posted by Alexey Dobriyan on Fri, 03 Aug 2007 13:30:18 GMT
View Forum Message <> Reply to Message

Driver does
 proc_mkdir("ipmi", NULL);
but
 remove_proc_entry(proc_ipmi_root->name, &proc_root);

This is OK and working if only slightly inconsistent.
Also changing proc_root to NULL will help OpenVZ which has
multiple proc roots and, as we now know, requires matching parents in
such cases.

Please, apply.

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>
---

 drivers/char/ipmi/ipmi_msghandler.c | 2 +-
 1 file changed, 1 insertion(+), 1 deletion(-)

--- a/drivers/char/ipmi/ipmi_msghandler.c
+++ b/drivers/char/ipmi/ipmi_msghandler.c
@@ -4136,7 +4136,7 @@ static __exit void cleanup_ipmi(void)
  del_timer_sync(&ipmi_timer);

 #ifdef CONFIG_PROC_FS
- remove_proc_entry(proc_ipmi_root->name, &proc_root);
+ remove_proc_entry(proc_ipmi_root->name, NULL);
 #endif /* CONFIG_PROC_FS */

  driver_unregister(&ipmidriver);