Subject: [PATCH] Fix check for return value of create_pid_namespace
Posted by Pavel Emelianov on Fri, 17 Aug 2007 09:25:40 GMT
View Forum Message <> Reply to Message

The function in question returns ERR_PTR-s to indicate the
error, while the caller checks for return value to be NULL.

Found during testing the OpenVZ kernel with pid namespaces.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>
Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>
Cc: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Oleg Nesterov <oleg@tv-sign.ru>

---
 kernel/pid.c | 2 +-
 1 files changed, 1 insertion(+), 1 deletion(-)

```
diff --git a/kernel/pid.c b/kernel/pid.c
index faad017..cb1f3cb 100644
--- a/kernel/pid.c
+++ b/kernel/pid.c
@@ -543,7 +543,7 @@ struct pid_namespace *copy_pid_ns(unsign
   goto out_put;

  new_ns = create_pid_namespace(old_ns->level + 1);
- if (new_ns != NULL)
+ if (!IS_ERR(new_ns))
   new_ns->parent = get_pid_ns(old_ns);

 out_put:
```