Subject: [RFC][PATCH 1/3]: Replace pid_t in autofs with struct pid reference.
Posted by Sukadev Bhattiprolu on Thu, 25 Jan 2007 03:53:31 GMT
View Forum Message <> Reply to Message

ChangeLog:
 - Fix Eric Biederman's comments - Use find_get_pid() to hold a
   reference to oz_pgrp and release while unmounting; separate out
   changes to autofs and autofs4.

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Subject: Replace pid_t in autofs with struct pid reference.

Make autofs container-friendly by caching struct pid reference rather
than pid_t.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: Eric Biederman <ebiederm@xmission.com>
Cc: containers@lists.osdl.org

---
 fs/autofs/autofs_i.h | 4 ++--
 fs/autofs/inode.c | 33 ++++++++++++++++++++++++---------
 fs/autofs/root.c | 6 ++++--
 3 files changed, 30 insertions(+), 13 deletions(-)

Index: lx26-20-rc4-mm1/fs/autofs/autofs_i.h
==========
--- lx26-20-rc4-mm1.orig/fs/autofs/autofs_i.h 2007-01-24 17:29:32.471909792 -0800
+++ lx26-20-rc4-mm1/fs/autofs/autofs_i.h 2007-01-24 17:31:10.277041152 -0800
@@ -101,7 +101,7 @@ struct autofs_symlink {
 struct autofs_sb_info {
  u32 magic;
  struct file *pipe;
- pid_t oz_pgrp;
+ struct pid *oz_pgrp;
  int catatonic;
  struct super_block *sb;
  unsigned long exp_timeout;
@@ -122,7 +122,7 @@ static inline struct autofs_sb_info *aut
   filesystem without "magic".) */

 static inline int autofs_oz_mode(struct autofs_sb_info *sbi) {
- return sbi->catatonic || process_group(current) == sbi->oz_pgrp;

```
+ return sbi->catatonic || task_pgrp(current) == sbi->oz_pgrp;
 }

 /* Hash operations */
Index: lx26-20-rc4-mm1/fs/autofs/inode.c
===================================================================
--- lx26-20-rc4-mm1.orig/fs/autofs/inode.c 2007-01-24 17:29:32.471909792 -0800
+++ lx26-20-rc4-mm1/fs/autofs/inode.c 2007-01-24 18:39:20.834181944 -0800
@@ -37,6 +37,8 @@ void autofs_kill_sb(struct super_block *
  if ( !sbi->catatonic )
   autofs_catatonic_mode(sbi); /* Free wait queues, close pipe */

+ put_pid(sbi->oz_pgrp);
+
  autofs_hash_nuke(sbi);
  for ( n = 0 ; n < AUTOFS_MAX_SYMLINKS ; n++ ) {
   if ( test_bit(n, sbi->symlink_bitmap) )
@@ -69,15 +71,17 @@ static match_table_t autofs_tokens = {
  {Opt_err, NULL}
 };

-static int parse_options(char *options, int *pipefd, uid_t *uid, gid_t *gid, pid_t *pgrp, int *minproto,
int *maxproto)
+static int parse_options(char *options, int *pipefd, uid_t *uid, gid_t *gid,
+   struct pid **pgrp, int *minproto, int *maxproto)
 {
  char *p;
  substring_t args[MAX_OPT_ARGS];
  int option;
+ pid_t pgid;

  *uid = current->uid;
  *gid = current->gid;
- *pgrp = process_group(current);
+ pgid = process_group(current);

  *minproto = *maxproto = AUTOFS_PROTO_VERSION;

@@ -111,7 +115,7 @@ static int parse_options(char *options,
    case Opt_pgrp:
     if (match_int(&args[0], &option))
      return 1;
-    *pgrp = option;
+    pgid = option;
     break;
    case Opt_minproto:
     if (match_int(&args[0], &option))
@@ -127,7 +131,13 @@ static int parse_options(char *options,
```

```
    return 1;
   }
  }
- return (*pipefd < 0);
+
+ if (*pipefd < 0)
+  return 1;
+
+ *pgrp = find_get_pid(pgid);
+
+ return (*pgrp == NULL);
 }

 int autofs_fill_super(struct super_block *s, void *data, int silent)
@@ -149,7 +159,7 @@ int autofs_fill_super(struct super_block
  sbi->pipe = NULL;
  sbi->catatonic = 1;
  sbi->exp_timeout = 0;
- sbi->oz_pgrp = process_group(current);
+ sbi->oz_pgrp = NULL;
  autofs_initialize_hash(&sbi->dirhash);
  sbi->queues = NULL;
  memset(sbi->symlink_bitmap, 0, sizeof(long)*AUTOFS_SYMLINK_BITMAP_LEN);
@@ -169,7 +179,9 @@ int autofs_fill_super(struct super_block
   goto fail_iput;

  /* Can this call block?  - WTF cares? s is locked. */
- if (
parse_options(data,&pipefd,&root_inode->i_uid,&root_inode->i_gid,&sbi->oz_pgrp,&minproto,&m
axproto) ) {
+ if ( parse_options(data, &pipefd, &root_inode->i_uid,
+     &root_inode->i_gid, &sbi->oz_pgrp, &minproto,
+     &maxproto) ) {
   printk("autofs: called with bogus options\n");
   goto fail_dput;
  }
@@ -178,15 +190,16 @@ int autofs_fill_super(struct super_block
  if ( minproto > AUTOFS_PROTO_VERSION ||
       maxproto < AUTOFS_PROTO_VERSION ) {
   printk("autofs: kernel does not match daemon version\n");
-  goto fail_dput;
+  goto fail_put_pid;
  }

- DPRINTK(("autofs: pipe fd = %d, pgrp = %u\n", pipefd, sbi->oz_pgrp));
+ DPRINTK(("autofs: pipe fd = %d, pgrp = %u\n", pipefd,
+     pid_nr(sbi->oz_pgrp)));
  pipe = fget(pipefd);
```

```
  if ( !pipe ) {
   printk("autofs: could not open pipe file descriptor\n");
-  goto fail_dput;
+  goto fail_put_pid;
  }
  if ( !pipe->f_op || !pipe->f_op->write )
   goto fail_fput;
@@ -202,6 +215,8 @@ int autofs_fill_super(struct super_block
 fail_fput:
  printk("autofs: pipe file descriptor does not contain proper ops\n");
  fput(pipe);
+fail_put_pid:
+ put_pid(sbi->oz_pgrp);
 fail_dput:
  dput(root);
  goto fail_free;
Index: lx26-20-rc4-mm1/fs/autofs/root.c
===================================================================
--- lx26-20-rc4-mm1.orig/fs/autofs/root.c 2007-01-24 17:29:32.471909792 -0800
+++ lx26-20-rc4-mm1/fs/autofs/root.c 2007-01-24 18:39:20.834181944 -0800
@@ -213,8 +213,10 @@ static struct dentry *autofs_root_lookup
  sbi = autofs_sbi(dir->i_sb);

  oz_mode = autofs_oz_mode(sbi);
- DPRINTK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, oz_mode = %d\n",
-   current->pid, process_group(current), sbi->catatonic, oz_mode));
+ DPRINTK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, "
+    "oz_mode = %d\n", pid_nr(task_pid(current)),
+    process_group(current), sbi->catatonic,
+    oz_mode));

  /*
   * Mark the dentry incomplete, but add it. This is needed so
```

_____
Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers

Subject: Re: [RFC][PATCH 1/3]: Replace pid_t in autofs with struct pid reference.
Posted by Cedric Le Goater on Thu, 25 Jan 2007 15:30:41 GMT
View Forum Message <> Reply to Message

comments below,

Sukadev Bhattiprolu wrote:
> ChangeLog:

> - Fix Eric Biederman's comments - Use find_get_pid() to hold a
>   reference to oz_pgrp and release while unmounting; separate out
>   changes to autofs and autofs4.
> ---
>
> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
>
> Subject: Replace pid_t in autofs with struct pid reference.
>
> Make autofs container-friendly by caching struct pid reference rather
> than pid_t.
>
> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> Cc: Cedric Le Goater <clg@fr.ibm.com>
> Cc: Dave Hansen <haveblue@us.ibm.com>
> Cc: Serge Hallyn <serue@us.ibm.com>
> Cc: Eric Biederman <ebiederm@xmission.com>
> Cc: containers@lists.osdl.org
>
> ---
> fs/autofs/autofs_i.h | 4 ++--
> fs/autofs/inode.c | 33 +++++++++++++++++++++++++---------
> fs/autofs/root.c | 6 ++++--
> 3 files changed, 30 insertions(+), 13 deletions(-)
>
> Index: lx26-20-rc4-mm1/fs/autofs/autofs_i.h
> ===
> --- lx26-20-rc4-mm1.orig/fs/autofs/autofs_i.h 2007-01-24 17:29:32.471909792 -0800
> +++ lx26-20-rc4-mm1/fs/autofs/autofs_i.h 2007-01-24 17:31:10.277041152 -0800
> @@ -101,7 +101,7 @@ struct autofs_symlink {
> struct autofs_sb_info {
>   u32 magic;
>   struct file *pipe;
> - pid_t oz_pgrp;
> + struct pid *oz_pgrp;
>   int catatonic;
>   struct super_block *sb;
>   unsigned long exp_timeout;
> @@ -122,7 +122,7 @@ static inline struct autofs_sb_info *aut
>   filesystem without "magic".) */
>
> static inline int autofs_oz_mode(struct autofs_sb_info *sbi) {
> - return sbi->catatonic || process_group(current) == sbi->oz_pgrp;
> + return sbi->catatonic || task_pgrp(current) == sbi->oz_pgrp;
> }
>
> /* Hash operations */
> Index: lx26-20-rc4-mm1/fs/autofs/inode.c

```
> ===================================================================
> --- lx26-20-rc4-mm1.orig/fs/autofs/inode.c 2007-01-24 17:29:32.471909792 -0800
> +++ lx26-20-rc4-mm1/fs/autofs/inode.c 2007-01-24 18:39:20.834181944 -0800
> @@ -37,6 +37,8 @@ void autofs_kill_sb(struct super_block *
>   if ( !sbi->catatonic )
>    autofs_catatonic_mode(sbi); /* Free wait queues, close pipe */
>
> + put_pid(sbi->oz_pgrp);
> +
>   autofs_hash_nuke(sbi);
>   for ( n = 0 ; n < AUTOFS_MAX_SYMLINKS ; n++ ) {
>    if ( test_bit(n, sbi->symlink_bitmap) )
```

too many white spaces. may be you could fix those at the same time ?

```
> @@ -69,15 +71,17 @@ static match_table_t autofs_tokens = {
>   {Opt_err, NULL}
>  };
>
> -static int parse_options(char *options, int *pipefd, uid_t *uid, gid_t *gid, pid_t *pgrp, int
*minproto, int *maxproto)
> +static int parse_options(char *options, int *pipefd, uid_t *uid, gid_t *gid,
> +  struct pid **pgrp, int *minproto, int *maxproto)
>  {
>   char *p;
>   substring_t args[MAX_OPT_ARGS];
>   int option;
> + pid_t pgid;
>
>   *uid = current->uid;
>   *gid = current->gid;
> - *pgrp = process_group(current);
> + pgid = process_group(current);
>
>   *minproto = *maxproto = AUTOFS_PROTO_VERSION;
>
> @@ -111,7 +115,7 @@ static int parse_options(char *options,
>    case Opt_pgrp:
>     if (match_int(&args[0], &option))
>      return 1;
> -   *pgrp = option;
> +   pgid = option;
>     break;
>    case Opt_minproto:
>     if (match_int(&args[0], &option))
> @@ -127,7 +131,13 @@ static int parse_options(char *options,
>     return 1;
>    }
```

>   }
> - return (*pipefd < 0);
> +
> + if (*pipefd < 0)
> + return 1;
> +
> + *pgrp = find_get_pid(pgid);
> +
> + return (*pgrp == NULL);
> }
>
> int autofs_fill_super(struct super_block *s, void *data, int silent)
> @@ -149,7 +159,7 @@ int autofs_fill_super(struct super_block
>   sbi->pipe = NULL;
>   sbi->catatonic = 1;
>   sbi->exp_timeout = 0;
> - sbi->oz_pgrp = process_group(current);
> + sbi->oz_pgrp = NULL;
>   autofs_initialize_hash(&sbi->dirhash);
>   sbi->queues = NULL;
>   memset(sbi->symlink_bitmap, 0, sizeof(long)*AUTOFS_SYMLINK_BITMAP_LEN);
> @@ -169,7 +179,9 @@ int autofs_fill_super(struct super_block
>   goto fail_iput;
>
>   /* Can this call block? - WTF cares? s is locked. */
> - if (
parse_options(data,&pipefd,&root_inode->i_uid,&root_inode->i_gid,&sbi->oz_pgrp,&minproto,&m
axproto)) {
> + if (parse_options(data, &pipefd, &root_inode->i_uid,
> +   &root_inode->i_gid, &sbi->oz_pgrp, &minproto,
> +   &maxproto)) {

I would keep the old prototype of parse_options

>   printk("autofs: called with bogus options\n");
>   goto fail_dput;
>   }

and do the find_get_pid() here. it looks simpler for me.

> @@ -178,15 +190,16 @@ int autofs_fill_super(struct super_block
>   if (minproto > AUTOFS_PROTO_VERSION ||
>   maxproto < AUTOFS_PROTO_VERSION) {
>   printk("autofs: kernel does not match daemon version\n");
> - goto fail_dput;
> + goto fail_put_pid;
>   }
>

> - DPRINTK(("autofs: pipe fd = %d, pgrp = %u\n", pipefd, sbi->oz_pgrp));
> + DPRINTK(("autofs: pipe fd = %d, pgrp = %u\n", pipefd,
> +   pid_nr(sbi->oz_pgrp)));
>   pipe = fget(pipefd);
>
>   if (!pipe) {
>   printk("autofs: could not open pipe file descriptor\n");
> - goto fail_dput;
> + goto fail_put_pid;
>   }
>   if (!pipe->f_op || !pipe->f_op->write)
>   goto fail_fput;
> @@ -202,6 +215,8 @@ int autofs_fill_super(struct super_block
> fail_fput:
>   printk("autofs: pipe file descriptor does not contain proper ops\n");
>   fput(pipe);
> +fail_put_pid:
> + put_pid(sbi->oz_pgrp);
> fail_dput:
>   dput(root);
>   goto fail_free;
> Index: lx26-20-rc4-mm1/fs/autofs/root.c
> ===
> --- lx26-20-rc4-mm1.orig/fs/autofs/root.c 2007-01-24 17:29:32.471909792 -0800
> +++ lx26-20-rc4-mm1/fs/autofs/root.c 2007-01-24 18:39:20.834181944 -0800
> @@ -213,8 +213,10 @@ static struct dentry *autofs_root_lookup
>   sbi = autofs_sbi(dir->i_sb);
>
>   oz_mode = autofs_oz_mode(sbi);
> - DPRINTK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, oz_mode = %d\n",
> -   current->pid, process_group(current), sbi->catatonic, oz_mode));
> + DPRINTK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, "
> +   "oz_mode = %d\n", pid_nr(task_pid(current)),
> +   process_group(current), sbi->catatonic,
> +   oz_mode));

you can keep current->pid I think

>   /*
>   * Mark the dentry incomplete, but add it. This is needed so
> _____
> Containers mailing list
> Containers@lists.osdl.org
> https://lists.osdl.org/mailman/listinfo/containers
>

_____

Subject: Re: [RFC][PATCH 1/3]: Replace pid_t in autofs with struct pid reference.
Posted by Sukadev Bhattiprolu on Fri, 26 Jan 2007 03:11:15 GMT
View Forum Message <> Reply to Message

Cedric Le Goater [clg@fr.ibm.com] wrote:
| comments below,
|
| > autofs_hash_nuke(sbi);
| > for (n = 0 ; n < AUTOFS_MAX_SYMLINKS ; n++) {
| > if (test_bit(n, sbi->symlink_bitmap))
|
| too many white spaces. may be you could fix those at the same time ?

There are too many of those errors in the autofs/autofs4 files. I am
moving all those changes to a separate patch so the main patch stays
small. Let me know if thats a bad idea.

| > + if (parse_options(data, &pipefd, &root_inode->i_uid,
| > + &root_inode->i_gid, &sbi->oz_pgrp, &minproto,
| > + &maxproto)) {
|
| I would keep the old prototype of parse_options
|
| > printk("autofs: called with bogus options\n");
| > goto fail_dput;
| > }
|
| and do the find_get_pid() here. it looks simpler for me.

Agree.

| > + DPRINTK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, "
| > + "oz_mode = %d\n", pid_nr(task_pid(current)),
| > + process_group(current), sbi->catatonic,
| > + oz_mode));
|
|
| you can keep current->pid I think
|

I am not sure. If a process unshares its pid-ns and then used to automount
in the child ns, won't we print the wrong pid ?

_____

Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers