Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
Posted by Sukadev Bhattiprolu on Wed, 21 Mar 2007 03:24:17 GMT
View Forum Message <> Reply to Message

This was discussed on containers and we thought it would be useful
to reserve this flag.

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag

Define CLONE_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
---
 include/linux/sched.h | 1 +
 1 file changed, 1 insertion(+)

Index: 2.6.21-rc3-mm2/include/linux/sched.h
===
--- 2.6.21-rc3-mm2.orig/include/linux/sched.h
+++ 2.6.21-rc3-mm2/include/linux/sched.h
@@ -26,6 +26,7 @@
 #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
 #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
 #define CLONE_NEWIPC 0x08000000 /* New ipcs */
+#define CLONE_NEWPID 0x10000000   /* New pid namespace */

 /*
  * Scheduling policies

--

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers

Subject: Re: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
Posted by Cedric Le Goater on Wed, 21 Mar 2007 12:50:44 GMT
View Forum Message <> Reply to Message

sukadev@us.ibm.com wrote:
> This was discussed on containers and we thought it would be useful
> to reserve this flag.
> ---
>

> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
>
> Define CLONE_NEWPID flag that will be used to clone pid namespaces.
>
> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> ---
> include/linux/sched.h | 1 +
> 1 file changed, 1 insertion(+)
>
> Index: 2.6.21-rc3-mm2/include/linux/sched.h
> ===
> --- 2.6.21-rc3-mm2.orig/include/linux/sched.h
> +++ 2.6.21-rc3-mm2/include/linux/sched.h
> @@ -26,6 +26,7 @@
> #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
> #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
> #define CLONE_NEWIPC 0x08000000 /* New ipcs */
> +#define CLONE_NEWPID 0x10000000   /* New pid namespace */
>
> /*
>   * Scheduling policies
>

I think we can send this one to -mm.

thanks,

C.

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers

---

Subject: Re: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
Posted by ebiederm on Wed, 21 Mar 2007 17:30:14 GMT
View Forum Message <> Reply to Message

Cedric Le Goater <clg@fr.ibm.com> writes:

> sukadev@us.ibm.com wrote:
>> This was discussed on containers and we thought it would be useful
>> to reserve this flag.
>> ---
>>
>> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
>> Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag

>>
>> Define CLONE_NEWPID flag that will be used to clone pid namespaces.
>>
>> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
>> ---
>> include/linux/sched.h | 1 +
>> 1 file changed, 1 insertion(+)
>>
>> Index: 2.6.21-rc3-mm2/include/linux/sched.h
>> ===
>> --- 2.6.21-rc3-mm2.orig/include/linux/sched.h
>> +++ 2.6.21-rc3-mm2/include/linux/sched.h
>> @@ -26,6 +26,7 @@
>> #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
>> #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
>> #define CLONE_NEWIPC 0x08000000 /* New ipcs */
>> +#define CLONE_NEWPID 0x10000000   /* New pid namespace */
>>
>> /*
>>   * Scheduling policies
>>
>
> I think we can send this one to -mm.

Sounds good to me.

Eric

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers

---

Subject: Re: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
Posted by Herbert Poetzl on Fri, 23 Mar 2007 01:30:37 GMT
View Forum Message <> Reply to Message

On Wed, Mar 21, 2007 at 11:30:14AM -0600, Eric W. Biederman wrote:
> Cedric Le Goater <clg@fr.ibm.com> writes:
>
> > sukadev@us.ibm.com wrote:
> >> This was discussed on containers and we thought it would be useful
> >> to reserve this flag.
> >> ---
> >>
> >> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> >> Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
> >>

> >> Define CLONE_NEWPID flag that will be used to clone pid namespaces.
> >>
> >> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> >> ---
> >> include/linux/sched.h | 1 +
> >> 1 file changed, 1 insertion(+)
> >>
> >> Index: 2.6.21-rc3-mm2/include/linux/sched.h
> >> ===
> >> --- 2.6.21-rc3-mm2.orig/include/linux/sched.h
> >> +++ 2.6.21-rc3-mm2/include/linux/sched.h
> >> @@ -26,6 +26,7 @@
> >> #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
> >> #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
> >> #define CLONE_NEWIPC 0x08000000 /* New ipcs */
> >> +#define CLONE_NEWPID 0x10000000   /* New pid namespace */
> >>
> >> /*
> >>   * Scheduling policies
> >>
> >
> > I think we can send this one to -mm.
>
> Sounds good to me.

yep, we won't get around it :)

i.e. I'm fine with this

best,
Herbert

> Eric
> _____
> Containers mailing list
> Containers@lists.linux-foundation.org
> https://lists.linux-foundation.org/mailman/listinfo/containers

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers