Subject: [PATCH 10/17] Pid-NS(V3) Define CLONE_NEWPID flag
Posted by Sukadev Bhattiprolu on Sat, 16 Jun 2007 23:02:18 GMT
View Forum Message <> Reply to Message

Subject: [PATCH 10/17] Pid-NS(V3) Define CLONE_NEWPID flag

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

This was discussed on containers and we thought it would be useful
to reserve this flag.

TODO: Merge this with the next patch ?

Define CLONE_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
---
 include/linux/sched.h | 1 +
 1 file changed, 1 insertion(+)

Index: lx26-22-rc4-mm2/include/linux/sched.h
==========
--- lx26-22-rc4-mm2.orig/include/linux/sched.h 2007-06-15 19:47:58.000000000 -0700
+++ lx26-22-rc4-mm2/include/linux/sched.h 2007-06-15 19:48:24.000000000 -0700
@@ -25,6 +25,7 @@
 #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
 #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
 #define CLONE_NEWIPC 0x08000000 /* New ipcs */
+#define CLONE_NEWPID 0x20000000   /* New pid namespace */

 /*
  * Scheduling policies

--

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers