
Subject: [PATCH] Remove write-only variable from pktgen_thread
Posted by [Pavel Emelianov](#) on Wed, 29 Aug 2007 13:22:02 GMT
[View Forum Message](#) <> [Reply to Message](#)

The pktgen_thread.pid is set to current->pid and is never used after this. So remove this at all.

Found during isolating the explicit pid/tgid usage.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/core/pktgen.c b/net/core/pktgen.c
index 3a3154e..93695c2 100644
--- a/net/core/pktgen.c
+++ b/net/core/pktgen.c
@@ -380,7 +380,6 @@ struct pktgen_thread {
     /* Field for thread to receive "posted" events terminate, stop ifs etc. */

    u32 control;
-   int pid;
    int cpu;

    wait_queue_head_t queue;
@@ -3462,8 +3461,6 @@ static int pktgen_thread_worker(void *ar

    init_waitqueue_head(&t->queue);

-   t->pid = current->pid;
-
    pr_debug("pktgen: starting pktgen/%d: pid=%d\n", cpu, task_pid_nr(current));

    max_before_softirq = t->max_before_softirq;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
