Subject: [PATCH 3/3] user.c: #ifdef ->mq_bytes
Posted by Alexey Dobriyan on Fri, 21 Sep 2007 09:40:10 GMT
View Forum Message <> Reply to Message

for those who deselect POSIX message queues.

Reduces SLAB size of user_struct from 64 to 32 bytes here,
SLUB size -- from 40 bytes to 32 bytes.

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>
---

 include/linux/sched.h | 2 ++
 kernel/user.c | 2 --
 2 files changed, 2 insertions(+), 2 deletions(-)

--- a/include/linux/sched.h
+++ b/include/linux/sched.h
@@ -583,8 +583,10 @@ struct user_struct {
  atomic_t inotify_watches; /* How many inotify watches does this user have? */
  atomic_t inotify_devs; /* How many inotify devs does this user have opened? */
 #endif
+#ifdef CONFIG_POSIX_MQUEUE
  /* protected by mq_lock */
  unsigned long mq_bytes; /* How many bytes can be allocated to mqueue? */
+#endif
  unsigned long locked_shm; /* How many pages of mlocked shm ? */

 #ifdef CONFIG_KEYS
--- a/kernel/user.c
+++ b/kernel/user.c
@@ -44,7 +44,6 @@ struct user_struct root_user = {
  .processes = ATOMIC_INIT(1),
  .files = ATOMIC_INIT(0),
  .sigpending = ATOMIC_INIT(0),
- .mq_bytes = 0,
  .locked_shm   = 0,
 #ifdef CONFIG_KEYS
  .uid_keyring = &root_user_keyring,

Subject: Re: [PATCH 3/3] user.c: #ifdef ->mq_bytes
Posted by Cedric Le Goater on Fri, 21 Sep 2007 09:55:50 GMT
View Forum Message <> Reply to Message

Hello Alexey !

Alexey Dobriyan wrote:

> for those who deselect POSIX message queues.
>
> Reduces SLAB size of user_struct from 64 to 32 bytes here,
> SLUB size -- from 40 bytes to 32 bytes.
>
> Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>
> ---
>
> include/linux/sched.h | 2 ++
> kernel/user.c | 2 --
> 2 files changed, 2 insertions(+), 2 deletions(-)
>
> --- a/include/linux/sched.h
> +++ b/include/linux/sched.h
> @@ -583,8 +583,10 @@ struct user_struct {
>   atomic_t inotify_watches; /* How many inotify watches does this user have? */
>   atomic_t inotify_devs; /* How many inotify devs does this user have opened? */
> #endif
> +#ifdef CONFIG_POSIX_MQUEUE
>   /* protected by mq_lock */
>   unsigned long mq_bytes; /* How many bytes can be allocated to mqueue? */
> +#endif
>   unsigned long locked_shm; /* How many pages of mlocked shm ? */

while you are it, it seems possible to #ifdef locked_shm also. it's a bit more
complex because the code is mm/ and there are some links with the hugetlbfs
also.

Cheers,

C.

> #ifdef CONFIG_KEYS
> --- a/kernel/user.c
> +++ b/kernel/user.c
> @@ -44,7 +44,6 @@ struct user_struct root_user = {
>   .processes = ATOMIC_INIT(1),
>   .files = ATOMIC_INIT(0),
>   .sigpending = ATOMIC_INIT(0),
> - .mq_bytes = 0,
>   .locked_shm   = 0,
> #ifdef CONFIG_KEYS
>   .uid_keyring = &root_user_keyring,
>
> -
> To unsubscribe from this list: send the line "unsubscribe linux-kernel" in
> the body of a message to majordomo@vger.kernel.org
> More majordomo info at http://vger.kernel.org/majordomo-info.html

> Please read the FAQ at http://www.tux.org/lkml/
>