Subject: [PATCH 3/5] cleanup 3rd argument in netlink_sendskb
Posted by den on Fri, 05 Oct 2007 14:45:18 GMT
View Forum Message <> Reply to Message

netlink_sendskb does not use third argument. Clean it and save a couple of
bytes.

Signed-off-by: Denis V. Lunev <den@openvz.org>
Acked-by: Alexey Kuznetsov <kuznet@ms2.inr.ac.ru>

```
--- ./include/linux/netlink.h.nlk5 2007-08-26 19:30:37.000000000 +0400
+++ ./include/linux/netlink.h 2007-10-02 11:53:09.000000000 +0400
@@ -194,7 +194,7 @@ struct sock *netlink_getsockbyfilp(struc
 int netlink_attachskb(struct sock *sk, struct sk_buff *skb, int nonblock,
   long timeo, struct sock *ssk);
 void netlink_detachskb(struct sock *sk, struct sk_buff *skb);
-int netlink_sendskb(struct sock *sk, struct sk_buff *skb, int protocol);
+int netlink_sendskb(struct sock *sk, struct sk_buff *skb);

 /*
  * skb should fit one page. This choice is good for headerless malloc.
--- ./ipc/mqueue.c.nlk5 2007-08-26 19:30:37.000000000 +0400
+++ ./ipc/mqueue.c 2007-10-02 11:52:27.000000000 +0400
@@ -521,8 +521,7 @@ static void __do_notify(struct mqueue_in
    break;
   case SIGEV_THREAD:
    set_cookie(info->notify_cookie, NOTIFY_WOKENUP);
-   netlink_sendskb(info->notify_sock,
-     info->notify_cookie, 0);
+   netlink_sendskb(info->notify_sock, info->notify_cookie);
    break;
   }
   /* after notification unregisters process */
@@ -568,7 +567,7 @@ static void remove_notification(struct m
  if (info->notify_owner != NULL &&
      info->notify.sigev_notify == SIGEV_THREAD) {
   set_cookie(info->notify_cookie, NOTIFY_REMOVED);
-  netlink_sendskb(info->notify_sock, info->notify_cookie, 0);
+  netlink_sendskb(info->notify_sock, info->notify_cookie);
  }
  put_pid(info->notify_owner);
  info->notify_owner = NULL;
--- ./net/netlink/af_netlink.c.nlk5 2007-10-02 11:43:09.000000000 +0400
+++ ./net/netlink/af_netlink.c 2007-10-02 11:50:19.000000000 +0400
@@ -796,7 +796,7 @@ int netlink_attachskb(struct sock *sk, s
  return 0;
 }
```

```
-int netlink_sendskb(struct sock *sk, struct sk_buff *skb, int protocol)
+int netlink_sendskb(struct sock *sk, struct sk_buff *skb)
 {
  int len = skb->len;

@@ -858,7 +858,7 @@ retry:
  if (err)
   return err;

- return netlink_sendskb(sk, skb, ssk->sk_protocol);
+ return netlink_sendskb(sk, skb);
 }

 int netlink_has_listeners(struct sock *sk, unsigned int group)
```

Subject: Re: [PATCH 3/5] cleanup 3rd argument in netlink_sendskb
Posted by davem on Thu, 11 Oct 2007 04:14:09 GMT
View Forum Message <> Reply to Message

From: "Denis V. Lunev" <den@openvz.org>
Date: Fri, 5 Oct 2007 18:46:23 +0400

> netlink_sendskb does not use third argument. Clean it and save a couple of
> bytes.
>
> Signed-off-by: Denis V. Lunev <den@openvz.org>
> Acked-by: Alexey Kuznetsov <kuznet@ms2.inr.ac.ru>

Applied.
