
Subject: [PATCH 5/7] cgroup: fix subsys bitops
Posted by [Li Zefan](#) on Mon, 18 Feb 2008 05:49:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cgroup uses unsigned long for subsys bitops, not unsigned long long.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

kernel/cgroup.c | 4 ++--
1 files changed, 2 insertions(+), 2 deletions(-)

```
diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index aa76bbd..e8c8e58 100644
--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -320,7 +320,7 @@ static struct css_set *find_existing_css_set(
 /* Built the set of subsystem state objects that we want to
  * see in the new css_set */
 for (i = 0; i < CGROUP_SUBSYS_COUNT; i++) {
- if (root->subsys_bits & (1ull << i)) {
+ if (root->subsys_bits & (1UL << i)) {
 /* Subsystem is in this hierarchy. So we want
  * the subsystem state from the new
  * cgroup */
@@ -696,7 +696,7 @@ static int rebind_subsystems(struct cgroupfs_root *root,
 added_bits = final_bits & ~root->actual_subsys_bits;
 /* Check that any added subsystems are currently free */
 for (i = 0; i < CGROUP_SUBSYS_COUNT; i++) {
- unsigned long long bit = 1ull << i;
+ unsigned long bit = 1UL << i;
 struct cgroup_subsys *ss = subsys[i];
 if (!(bit & added_bits))
 continue;
--
1.5.4.rc3
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH 5/7] cgroup: fix subsys bitops
Posted by [Paul Menage](#) on Wed, 20 Feb 2008 02:57:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Feb 17, 2008 9:49 PM, Li Zefan <lizf@cn.fujitsu.com> wrote:
> Cgroup uses unsigned long for subsys bitops, not unsigned long long.

>

> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: Paul Menage <menage@google.com>

> ---

> kernel/cgroup.c | 4 ++--

> 1 files changed, 2 insertions(+), 2 deletions(-)

>

> diff --git a/kernel/cgroup.c b/kernel/cgroup.c

> index aa76bbd..e8c8e58 100644

> --- a/kernel/cgroup.c

> +++ b/kernel/cgroup.c

> @@ -320,7 +320,7 @@ static struct css_set *find_existing_css_set(

> /* Built the set of subsystem state objects that we want to

> * see in the new css_set */

> for (i = 0; i < CGROUP_SUBSYS_COUNT; i++) {

> - if (root->subsys_bits & (1ull << i)) {

> + if (root->subsys_bits & (1UL << i)) {

> /* Subsystem is in this hierarchy. So we want

> * the subsystem state from the new

> * cgroup */

> @@ -696,7 +696,7 @@ static int rebind_subsystems(struct cgroupfs_root *root,

> added_bits = final_bits & ~root->actual_subsys_bits;

> /* Check that any added subsystems are currently free */

> for (i = 0; i < CGROUP_SUBSYS_COUNT; i++) {

> - unsigned long long bit = 1ull << i;

> + unsigned long bit = 1UL << i;

> struct cgroup_subsys *ss = subsys[i];

> if (!(bit & added_bits))

> continue;

> --

> 1.5.4.rc3

>

>

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
