Subject: [PATCH 7/7] cgroup: remove dead code in cgroup_get_rootdir()
Posted by Li Zefan on Mon, 18 Feb 2008 05:50:01 GMT
View Forum Message <> Reply to Message

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>
---
 kernel/cgroup.c | 1 -
 1 files changed, 0 insertions(+), 1 deletions(-)

diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index 71cf961..879a056 100644
--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -926,7 +926,6 @@ static int cgroup_get_rootdir(struct super_block *sb)
  if (!inode)
   return -ENOMEM;

- inode->i_op = &simple_dir_inode_operations;
  inode->i_fop = &simple_dir_operations;
  inode->i_op = &cgroup_dir_inode_operations;
  /* directories start off with i_nlink == 2 (for "." entry) */
--
1.5.4.rc3

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers

Subject: Re: [PATCH 7/7] cgroup: remove dead code in cgroup_get_rootdir()
Posted by Paul Menage on Thu, 21 Feb 2008 00:47:20 GMT
View Forum Message <> Reply to Message

2008/2/17 Li Zefan <lizf@cn.fujitsu.com>:
> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: Paul Menage <menage@google.com>

> ---
> kernel/cgroup.c | 1 -
> 1 files changed, 0 insertions(+), 1 deletions(-)
>
> diff --git a/kernel/cgroup.c b/kernel/cgroup.c
> index 71cf961..879a056 100644
> --- a/kernel/cgroup.c
> +++ b/kernel/cgroup.c
> @@ -926,7 +926,6 @@ static int cgroup_get_rootdir(struct super_block *sb)

```
>         if (!inode)
>                 return -ENOMEM;
>
> -       inode->i_op = &simple_dir_inode_operations;
>         inode->i_fop = &simple_dir_operations;
>         inode->i_op = &cgroup_dir_inode_operations;
>         /* directories start off with i_nlink == 2 (for "." entry) */
> --
> 1.5.4.rc3
>
>
```

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers