
Subject: [PATCH] cgroup: fix default notify_on_release setting
Posted by [Li Zefan](#) on Mon, 25 Feb 2008 05:53:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

The documentation says the default value of notify_on_release of a child cgroup is inherited from its parent, which is reasonable, but the implementation just sets the flag disabled.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

kernel/cgroup.c | 4 +++-
1 files changed, 3 insertions(+), 1 deletions(-)

diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index d8abe99..e9c2fb0 100644
--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -2232,7 +2232,6 @@ static long cgroup_create(struct cgroup *parent, struct dentry *dentry,

mutex_lock(&cgroup_mutex);

- cgrp->flags = 0;
INIT_LIST_HEAD(&cgrp->sibling);
INIT_LIST_HEAD(&cgrp->children);
INIT_LIST_HEAD(&cgrp->css_sets);
@@ -2242,6 +2241,9 @@ static long cgroup_create(struct cgroup *parent, struct dentry *dentry,
cgrp->root = parent->root;
cgrp->top_cgroup = parent->top_cgroup;

+ if (notify_on_release(parent))
+ set_bit(CGRP_NOTIFY_ON_RELEASE, &cgrp->flags);
+
for_each_subsys(root, ss) {
struct cgroup_subsys_state *css = ss->create(ss, cgrp);
if (IS_ERR(css)) {
--
1.5.4.rc3

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
