Subject: [PATCH 2/7][v2]: Factor out PTY index allocation
Posted by Sukadev Bhattiprolu on Thu, 03 Apr 2008 07:08:04 GMT
View Forum Message <> Reply to Message

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH 2/7][v2]: Factor out PTY index allocation

Factor out the code used to allocate/free a pts index into new interfaces,
devpts_new_index() and devpts_kill_index(). This localizes the external
data structures used in managing the pts indices.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Signed-off-by: Serge Hallyn<serue@us.ibm.com>
Signed-off-by: Matt Helsley<matthltc@us.ibm.com>

---
 drivers/char/tty_io.c | 40 ++++++----------------------------
 fs/devpts/inode.c | 42 ++++++++++++++++++++++++++++++++++++-
 include/linux/devpts_fs.h | 4 ++++
 3 files changed, 51 insertions(+), 35 deletions(-)

Index: 2.6.25-rc5-mm1/include/linux/devpts_fs.h
===
--- 2.6.25-rc5-mm1.orig/include/linux/devpts_fs.h 2008-03-24 20:04:07.000000000 -0700
+++ 2.6.25-rc5-mm1/include/linux/devpts_fs.h 2008-03-24 20:04:26.000000000 -0700
@@ -17,6 +17,8 @@

 #ifdef CONFIG_UNIX98_PTYS

+int devpts_new_index(void);
+void devpts_kill_index(int idx);
 int devpts_pty_new(struct tty_struct *tty);   /* mknod in devpts */
 struct tty_struct *devpts_get_tty(int number); /* get tty structure */
 void devpts_pty_kill(int number);   /* unlink */
@@ -24,6 +26,8 @@ void devpts_pty_kill(int number);   /* u
 #else

 /* Dummy stubs in the no-pty case */
+static inline int devpts_new_index(void) { return -EINVAL; }
+static inline void devpts_kill_index(int idx) { }
 static inline int devpts_pty_new(struct tty_struct *tty) { return -EINVAL; }
 static inline struct tty_struct *devpts_get_tty(int number) { return NULL; }
 static inline void devpts_pty_kill(int number) { }
Index: 2.6.25-rc5-mm1/drivers/char/tty_io.c
===
--- 2.6.25-rc5-mm1.orig/drivers/char/tty_io.c 2008-03-24 20:04:07.000000000 -0700
+++ 2.6.25-rc5-mm1/drivers/char/tty_io.c 2008-03-24 20:04:26.000000000 -0700
@@ -91,7 +91,6 @@

```
 #include <linux/module.h>
 #include <linux/smp_lock.h>
 #include <linux/device.h>
-#include <linux/idr.h>
 #include <linux/wait.h>
 #include <linux/bitops.h>
 #include <linux/delay.h>
@@ -137,9 +136,6 @@ EXPORT_SYMBOL(tty_mutex);

 #ifdef CONFIG_UNIX98_PTYS
 extern struct tty_driver *ptm_driver; /* Unix98 pty masters; for /dev/ptmx */
-extern int pty_limit;   /* Config limit on Unix98 ptys */
-static DEFINE_IDR(allocated_ptys);
-static DEFINE_MUTEX(allocated_ptys_lock);
 static int ptmx_open(struct inode *, struct file *);
 #endif

@@ -2636,15 +2632,9 @@ static void release_dev(struct file *fil
   */
  release_tty(tty, idx);

-#ifdef CONFIG_UNIX98_PTYS
  /* Make this pty number available for reallocation */
- if (devpts) {
-  mutex_lock(&allocated_ptys_lock);
-  idr_remove(&allocated_ptys, idx);
-  mutex_unlock(&allocated_ptys_lock);
- }
-#endif
-
+ if (devpts)
+  devpts_kill_index(idx);
 }

 /**
@@ -2800,29 +2790,13 @@ static int ptmx_open(struct inode *inode
  struct tty_struct *tty;
  int retval;
  int index;
- int idr_ret;

  nonseekable_open(inode, filp);

  /* find a device that is not in use. */
- mutex_lock(&allocated_ptys_lock);
- if (!idr_pre_get(&allocated_ptys, GFP_KERNEL)) {
-  mutex_unlock(&allocated_ptys_lock);
-  return -ENOMEM;
```

```
- }
- idr_ret = idr_get_new(&allocated_ptys, NULL, &index);
- if (idr_ret < 0) {
-  mutex_unlock(&allocated_ptys_lock);
-  if (idr_ret == -EAGAIN)
-   return -ENOMEM;
-  return -EIO;
- }
- if (index >= pty_limit) {
-  idr_remove(&allocated_ptys, index);
-  mutex_unlock(&allocated_ptys_lock);
-  return -EIO;
- }
- mutex_unlock(&allocated_ptys_lock);
+ index = devpts_new_index();
+ if (index < 0)
+  return index;

  mutex_lock(&tty_mutex);
  retval = init_dev(ptm_driver, index, &tty);
@@ -2847,9 +2821,7 @@ out1:
  release_dev(filp);
  return retval;
 out:
- mutex_lock(&allocated_ptys_lock);
- idr_remove(&allocated_ptys, index);
- mutex_unlock(&allocated_ptys_lock);
+ devpts_kill_index(index);
  return retval;
 }
 #endif
Index: 2.6.25-rc5-mm1/fs/devpts/inode.c
===================================================================
--- 2.6.25-rc5-mm1.orig/fs/devpts/inode.c 2008-03-24 20:04:07.000000000 -0700
+++ 2.6.25-rc5-mm1/fs/devpts/inode.c 2008-03-24 20:04:26.000000000 -0700
@@ -17,6 +17,7 @@
 #include <linux/namei.h>
 #include <linux/mount.h>
 #include <linux/tty.h>
+#include <linux/idr.h>
 #include <linux/devpts_fs.h>
 #include <linux/parser.h>
 #include <linux/fsnotify.h>
@@ -26,6 +27,10 @@

 #define DEVPTS_DEFAULT_MODE 0600

+extern int pty_limit;   /* Config limit on Unix98 ptys */
```

```
+static DEFINE_IDR(allocated_ptys);
+static DECLARE_MUTEX(allocated_ptys_lock);
+
 static struct vfsmount *devpts_mnt;
 static struct dentry *devpts_root;

@@ -171,9 +176,44 @@ static struct dentry *get_node(int num)
  return lookup_one_len(s, root, sprintf(s, "%d", num));
 }

+int devpts_new_index(void)
+{
+ int index;
+ int idr_ret;
+
+retry:
+ if (!idr_pre_get(&allocated_ptys, GFP_KERNEL)) {
+  return -ENOMEM;
+ }
+
+ down(&allocated_ptys_lock);
+ idr_ret = idr_get_new(&allocated_ptys, NULL, &index);
+ if (idr_ret < 0) {
+  up(&allocated_ptys_lock);
+  if (idr_ret == -EAGAIN)
+   goto retry;
+  return -EIO;
+ }
+
+ if (index >= pty_limit) {
+  idr_remove(&allocated_ptys, index);
+  up(&allocated_ptys_lock);
+  return -EIO;
+ }
+ up(&allocated_ptys_lock);
+ return index;
+}
+
+void devpts_kill_index(int idx)
+{
+ down(&allocated_ptys_lock);
+ idr_remove(&allocated_ptys, idx);
+ up(&allocated_ptys_lock);
+}
+
 int devpts_pty_new(struct tty_struct *tty)
 {
- int number = tty->index;
```

```
+ int number = tty->index; /* tty layer puts index from devpts_new_index() in here */
  struct tty_driver *driver = tty->driver;
  dev_t device = MKDEV(driver->major, driver->minor_start+number);
  struct dentry *dentry;
```

_____

Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers