Subject: [PATCH] Add O_TRUNC when creating cryo file
Posted by Sukadev Bhattiprolu on Tue, 24 Jun 2008 22:49:57 GMT
View Forum Message <> Reply to Message

>From 9b4dff531586c8dd0b0c75b17ef9ea3e5efc4d0e Mon Sep 17 00:00:00 2001
From: Sukadev Bhattiprolu <sukadev@linux.vnet.ibm.com>
Date: Tue, 24 Jun 2008 15:42:55 -0700
Subject: [PATCH] Add O_TRUNC when creating cryo file

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
---
 cr.c | 2 +-
 1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/cr.c b/cr.c
index 96a2ea0..b688229 100644
--- a/cr.c
+++ b/cr.c
@@ -1966,7 +1966,7 @@ int main(int argc, char **argv)
   case 'l': mode = ch; break;
   case 's': cr_mode |= CR_STOP; break;
   case 'm': cr_mode |= CR_MMAP; break;
- case 'p': mode = ch; fd = 1; perm = O_WRONLY|O_CREAT; pid = (pid_t)atoi(optarg); break;
+ case 'p': mode = ch; fd = 1; perm = O_WRONLY|O_CREAT|O_TRUNC; pid =
(pid_t)atoi(optarg); break;
   case 'r': mode = ch; break;
   case 'f': strncpy(filename, optarg, sizeof(filename)); break;
   default: usage(); exit(1);
--
1.5.2.5

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers

Subject: Re: [PATCH] Add O_TRUNC when creating cryo file
Posted by serue on Tue, 24 Jun 2008 23:03:34 GMT
View Forum Message <> Reply to Message

Quoting sukadev@us.ibm.com (sukadev@us.ibm.com):
> >From 9b4dff531586c8dd0b0c75b17ef9ea3e5efc4d0e Mon Sep 17 00:00:00 2001
> From: Sukadev Bhattiprolu <sukadev@linux.vnet.ibm.com>
> Date: Tue, 24 Jun 2008 15:42:55 -0700
> Subject: [PATCH] Add O_TRUNC when creating cryo file
>
> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Thanks, applied.

-serge

> ---
> cr.c | 2 +-
> 1 files changed, 1 insertions(+), 1 deletions(-)
>
> diff --git a/cr.c b/cr.c
> index 96a2ea0..b688229 100644
> --- a/cr.c
> +++ b/cr.c
> @@ -1966,7 +1966,7 @@ int main(int argc, char **argv)
>   case 'l': mode = ch; break;
>   case 's': cr_mode |= CR_STOP; break;
>   case 'm': cr_mode |= CR_MMAP; break;
> - case 'p': mode = ch; fd = 1; perm = O_WRONLY|O_CREAT; pid = (pid_t)atoi(optarg); break;
> + case 'p': mode = ch; fd = 1; perm = O_WRONLY|O_CREAT|O_TRUNC; pid =
(pid_t)atoi(optarg); break;
>   case 'r': mode = ch; break;
>   case 'f': strncpy(filename, optarg, sizeof(filename)); break;
>   default: usage(); exit(1);
> --
> 1.5.2.5

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers