Subject: Suse VPS mount issues
Posted by rollinw on Fri, 07 Jul 2006 15:44:03 GMT
View Forum Message <> Reply to Message

After creating VPSs for 2 Suse templates (suse-9.3-x86_64 and opensuse-10-x86_64-default) I found that both showed incorrect mount information, both from the df -k command and the mount command. In both cases the /etc/fstab file had the wrong information.

I searched for evidence that others had found this problem, but didn't find any reports or posts. The answer to my problem was found in the document on Slackware Template Creation.

http://wiki.openvz.org/Slackware_template_creation

Before making the changes described below, one should stop
the VPS, if it is running:

```
/usr/sbin/vzctl stop nnn
```

Look in the document section,
Preparing the new VE
Getting the filesystem ready to run in a VE.
"Delete the file /etc/mtab and make it a symlink to
/proc/mounts"

This is the key to solving the problem, because the VPS needs to get its mount information from /proc/mounts

```
rm /vz/private/nnn/etc/mtab
ln -s /proc/mounts /vz/private/nnn/etc/mtab
```

Clean the /etc/fstab file

```
echo -n > /vz/private/nnn/etc/fstab
```

Slightly slower ways to accomplish the same goal are 1) edit the fstab file manually and delete all lines, or 2) with the
commands:

```
rm -f /vz/private/nnn/etc/fstab
touch /vz/private/nnn/etc/fstab
(make sure the permissions on the new empty fstab file are the
 same as on the old one)
```

Edit /etc/rc.d/rc.S

It was necessary to modify the procedure slightly because of minor differences between Slackware and Suse. Suse does not have an rc.S file. Instead it uses script files whose names start with bootxxx. Suse has 2 files in /etc/rc.d/ that need to be edited; these are bootlocalfs and

bootrootfsck. The edit action is almost the same: put a # character before any line that has

rm -f /etc/mtab(*)

In one of these files, the line containing the remove command had some other files as well. I deleted /etc/mtab from this list.

The Slackware document contains a number of other procedures too, but I was primarily interested in solving the mount problem.

After the changes are made, the VPS can be started:

/usr/sbin/vzctl start nnn

Log into the VPS with ssh.

Check the file /etc/fstab to make sure it is still empty:

cat /etc/fstab

Check that the link exists from /proc/mounts to /etc/mtab

ls -l /etc/mtab

Verify that mount and df -k correctly show that simfs is mounted on / (the root filesystem) and has the correct disk allocation.

Good luck
rollinw

Subject: Re: Suse VPS mount issues
Posted by dev on Mon, 10 Jul 2006 20:59:42 GMT
View Forum Message <> Reply to Message

Can you post this please on http://wiki.openvz.org into troubleshooting as something like "Wrong mount information inside VE"?

thanks in advance!
