Posted by RXL_ on Wed, 11 Aug 2010 18:04:03 GMT
View Forum Message <> Reply to Message

VE: CentOS 5.5 x86.
ovzkernel: 2.6.18-194.8.1.el5.028stab070.2xen
vzctl: vzctl-3.0.24.1-1

saslauthd.

Quote:CT: 190: started
device veth190.0 entered promiscuous mode
br0: port 3(veth190.0) entering learning state
br0: port 3(veth190.0) entering learning state
veth190.0: no IPv6 routers present
br0: topology change detected, propagating
br0: port 3(veth190.0) entering forwarding state
br0: port 3(veth190.0) entering disabled state
device veth190.0 left promiscuous mode
br0: port 3(veth190.0) entering disabled state
CT: 190: stopped

Posted by maratrus on Fri, 13 Aug 2010 16:50:23 GMT
View Forum Message <> Reply to Message

Posted by RXL_ on Fri, 13 Aug 2010 17:47:32 GMT
View Forum Message <> Reply to Message

...

```
# brctl show
bridge name     bridge id               STP enabled     interfaces
br0             8000.001851ba0d46       no              veth190.0
                                                        eth0

# ip link show
4: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 100
    link/ether 00:25:90:00:f1:fc brd ff:ff:ff:ff:ff:ff
3: br0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/ether 00:18:51:ba:0d:46 brd ff:ff:ff:ff:ff:ff
51: veth190.0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/ether 00:18:51:ba:0d:46 brd ff:ff:ff:ff:ff:ff
```

...

```
NETIF="ifname=eth0,bridge=br0,host_ifname=veth190.0"
```

ip link set dev veth190.0 up
brctl addif br0 veth190.0

Posted by maratrus on Sun, 15 Aug 2010 14:36:28 GMT
View Forum Message <> Reply to Message

Posted by RXL_ on Sun, 15 Aug 2010 17:51:22 GMT
View Forum Message <> Reply to Message

Posted by maratrus on Mon, 16 Aug 2010 08:17:23 GMT
View Forum Message <> Reply to Message

Posted by RXL_ on Mon, 16 Aug 2010 08:51:19 GMT
View Forum Message <> Reply to Message